



EC30 Technical Accessory Guide




NOTE: This document is only for general reference. Solutions Pathway and related PMBs should be used for product availability, pricing, and final solution selection.






This document and the information contained therein (Information) are Zebra- confidential, and are provided under, and subject to, the confidentiality provision of your PartnerConnect agreement with Zebra. Any public disclosure (via posting on your website or otherwise) of the Information is strictly prohibited and will be considered a violation of your PartnerConnect agreement with Zebra.




* Zebra does not endorse or specifically recommend any **third-party products, accessories, or hardware**. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE.

Cradles/Charging

Cradles

Part Number	Picture	Description	Notes	Required Items
CRD-EC30-2SCHG1-01		2-Slot Charge Only Cradle	► Charges two EC30 units.	<ul style="list-style-type: none"> ► Power Supply (PWR-BGA12V50W0WW) ► DC Line Cord (CBL-DC-388A1-01) ► AC Line Cord (23844-00-00R)
CRD-EC30-10SC1-01		10-Slot Charge Only Cradle	► Cradle can be mounted on desktop or can be mounted on 19" rack using optional brackets listed below.	<ul style="list-style-type: none"> ► Power Supply (PWR-BGA12V108W0WW) ► DC Line Cord (CBL-DC-381A1-01) ► AC Line Cord (23844-00-00R)
CRD-EC30-10SLC1-01		10-Slot LOCKING Charge Only Cradle	<ul style="list-style-type: none"> ► Cradle can be mounted on desktop or can be mounted on 19" rack using optional brackets listed below. ► Release of device from cradle is controlled by the device. Colored green LED light around cradle slot indicates when device is unlocked. 	<ul style="list-style-type: none"> ► Power Supply (PWR-BGA12V108W0WW) ► DC Line Cord (CBL-DC-381A1-01) ► AC Line Cord (23844-00-00R)
BRKT-SCRD-SMRK-01		Multi-Slot Wall/Rack Mount Bracket	<ul style="list-style-type: none"> ► Allows for rack and wall mounting of one 10-Slot Charger. ► Bracket can be mounted on standard 19" network rack or on a wall. ► Cable routing slots & removable power supply holder tray. ► Adjustable tabs & screw mounts for easy hanging/installation. ► Adjustable orientations - horizontal, vertical, angled. ► See the Bluetooth-Generic Accessories TAG for info on 3rd party Network Racks that can be used for mounting this bracket. 	

BRKT-EC30-10SC1-01		High Density Multi-Slot Wall/Rack Mount Bracket	<ul style="list-style-type: none"> ► Allows for rack and wall mounting of one 10-Slot Charger. ► Bracket can be mounted on standard 19" network rack or on a wall. ► Bracket will hold cradle in vertical position with device displays facing up, scan engines facing out, to provide for higher density device mounting. ► See the Bluetooth-Generic Accessories TAG for info on 3rd party Network Racks that can be used for mounting this bracket. 	
ADP-TC7X-PLT-FX		5-Slot ShareCradle Mounting Bracket Adapter Plate for Honeywell	<ul style="list-style-type: none"> ► Allows Zebra Multi-Slot ShareCradles to be mounted on legacy Honeywell Flex Cradle Wall Mount Brackets (HON SKU #203-641-002). ► Includes hardware to attach plate to HON wall bracket and secure ShareCradle to plate. ► NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this cable. 	
Direct to Device Charging				
Part Number	Picture	Description	Notes	Required Items
CBL-TC5X-USBC2A-01		USB-C cable for Charging/Communication	<ul style="list-style-type: none"> ► USB-A to USB-C cable ► Attaches to USB-C port on the bottom of the device or to the Single Slot Base Charge-Only Cradle (TBD). ► Can be used to charge the EC30 via USB connections (PC, USB AC Wall Outlet adapter, USB Cigarette Lighter adapter) ► Cable length is 1.5M (~5 ft.) ► Can also be used to communicate with EC30 without using a Cradle. 	USB Power Adapter (PWR-WUA5V12W0US - or country specific version)
CBL-TC2X-USBC-01		USB-C cable for Charging/Communication	<ul style="list-style-type: none"> ► USB-A to USB-C cable ► Attaches to USB-C port on the bottom of the device or to the Single Slot Base Charge-Only Cradle (TBD). ► Can be used to charge the EC30 via USB connections (PC, USB AC Wall Outlet adapter, USB Cigarette Lighter adapter) ► Cable length is 1.5M (~5 ft.) ► Can also be used to communicate with EC30 without using a Cradle. ► NOTE: This cable includes an additional ferrite bead. Use CBL-TC5X-USBC2A-01 for a lower profile cable. 	USB Power Adapter (PWR-WUA5V12W0US - or country specific version)
3rd party *		USB-C cable for Charging/Communication	<ul style="list-style-type: none"> ► USB-A to USB-C cable ► Attaches to USB-C port on the bottom of the device or to the Single Slot Base Charge-Only Cradle (TBD). ► Can be used to charge the EC30 via USB connections (PC, USB AC Wall Outlet adapter, USB Cigarette Lighter adapter) ► Cable length is 1.5M (~5 ft.) ► Can also be used to communicate with EC30 without using a Cradle. 	USB Power Adapter (PWR-WUA5V12W0US - or country specific version)

Communication Cables				
Part Number	Picture	Description	Notes	Required Items
CBL-TC5X-USBC2A-01		USB-C cable for Charging/Communication	<ul style="list-style-type: none"> ► USB-A to USB-C cable ► Attaches to USB-C port on the bottom of the device or to the Single Slot Base Charge-Only Cradle (TBD). ► Can be used to charge the EC30 via USB connections (PC, USB AC Wall Outlet adapter, USB Cigarette Lighter adapter) ► Cable length is 1.5M (~5 ft.) ► Can also be used to communicate with EC30 without using a Cradle. 	USB Power Adapter (PWR-WUA5V12W0US - or country specific version)
CBL-TC2X-USBC-01		USB-C cable for Charging/Communication	<ul style="list-style-type: none"> ► USB-A to USB-C cable ► Attaches to USB-C port on the bottom of the device or to the Single Slot Base Charge-Only Cradle (TBD). ► Can be used to charge the EC30 via USB connections (PC, USB AC Wall Outlet adapter, USB Cigarette Lighter adapter) ► Cable length is 1.5M (~5 ft.) ► Can also be used to communicate with EC30 without using a Cradle. ► NOTE: This cable includes an additional ferrite bead. Use CBL-TC5X-USBC2A-01 for a lower profile cable. 	USB Power Adapter (PWR-WUA5V12W0US - or country specific version)
3rd party *		USB-C cable for Charging/Communication	<ul style="list-style-type: none"> ► USB-A to USB-C cable ► Attaches to USB-C port on the bottom of the device or to the Single Slot Base Charge-Only Cradle (TBD). ► Can be used to charge the EC30 via USB connections (PC, USB AC Wall Outlet adapter, USB Cigarette Lighter adapter) ► Cable length is 1.5M (~5 ft.) ► Can also be used to communicate with EC30 without using a Cradle. 	USB Power Adapter (PWR-WUA5V12W0US - or country specific version)
Soft Goods/Wearables				
Part Number	Picture	Description	Notes	Required Items



<p>SG-EC30-ADP1-01</p>	 <p>The image shows the SG-EC30-ADP1-01 Accessory Adapter, a black plastic device with a handle and a slot for the EC30 device. Below it is a small inset image showing the EC30 device attached to the adapter.</p>	<p>Accessory Adapter</p>	<ul style="list-style-type: none"> ► Holds the EC30 and is used with a variety of other accessories listed in this section. ► Black color 	
<p>SG-EC30-CLIP1-01</p>	 <p>The image shows the SG-EC30-CLIP1-01 Vest/Pocket Lanyard, a coiled lanyard with a clip at the top and a connector at the bottom. An inset image shows a person wearing a vest with the lanyard attached to their pocket.</p>	<p>Vest/Pocket Lanyard</p>	<ul style="list-style-type: none"> ► Tether in-pocket accessory uses coiled lanyard attached to Accessory Adapter. ► Prevents loss and drops of EC30 ► EC30 can be easily dropped in vest pocket or other garment pocket when not in use. ► Intuitive pocket clip anchors lanyard ► Uses Accessory Adapter (SG-EC30-ADP1-01) and clip-on coiled tether. 	

<p>SG-EC30-BLYD1-01 (single)</p> <p>SG-EC30-BLYD1-10 (pack of 10)</p>		<p>Basic Neck Lanyard</p>	<ul style="list-style-type: none"> ▶ Uses Accessory Adapter (SG-EC30-ADP1-01) and Neck Lanyard. ▶ Black color ▶ Lanyard has adjustable length and safety break-away. ▶ Length is adjustable between 16" and 30" ▶ Can be worn in short position around neck or at full length as a satchel. 	
<p>SG-EC30-RLYD1-01 (single)</p> <p>SG-EC30-RLYD1-10 (pack of 10)</p>		<p>Retractable Neck Lanyard</p>	<ul style="list-style-type: none"> ▶ Uses Accessory Adapter (SG-EC30-ADP1-01), Neck Lanyard and Magnetic Retractor (SG-EC30-RET1-01). ▶ Black color ▶ Familiar neck lanyard with unique magnetic "home holding feature" ▶ Extends to 30" with low pull-back to avoid "sling shot" retracting. ▶ Secondary clips reduce swinging of device when user bends over or leans forward. ▶ Lanyard has adjustable length and safety break-away 	



SG-EC30-RCB1-01		Retractable Belt Clip/Carabiner	<ul style="list-style-type: none"> ► Uses Accessory Adapter (SG-EC30-ADP1-01) and Magnetic Retractor (SG-EC30-RET1-01). ► Black color ► Carabiner can be attached to belt loop or other articles of clothing. ► Extends to 30" with low pull-back to avoid "sling shot" retracting. 	
SG-EC30-RET1-01		Spare/Replacement Magnetic Retractor		
SG-EC30-ARM1-01 (standard length strap - 12 inches) SG-EC30-ARML1-01 (long strap - 18 inches)		Arm/Wrist Mount	<ul style="list-style-type: none"> ► Allows EC30 to be worn on upper or lower portion of arm. ► Only one orientation supported ► Very light scanning possible ► Provides access to audio jack. ► Uses Velcro material 	

SG-EC30-HLSTR1-01		Soft Holster	<ul style="list-style-type: none"> ► Leather construction with protective flap and belt clip. 	
SG-EC30-RHLSTR1-01		Rigid Holster	<ul style="list-style-type: none"> ► Holster allows EC30 to be worn on belt ► Rotates to be used at any orientation ► EC30 can be inserted in any direction while still allowing access to the audio jack. 	




Misc




Part Number	Picture	Description	Notes	Required Items
SG-EC30-SCRNP1-05 (pack of 5)		Screen Protector	<ul style="list-style-type: none"> ► Tempered glass with oleophobic coating to reduce smudges. ► Includes wipes, cleaning cloth and installation instructions. 	
KT-MC18-CKEY-20		10-Slot LOCKING Cradle Release Tool	<ul style="list-style-type: none"> ► Used to mechanically unlock the EC30 from the 10-Slot LOCKING Cradle (CRD-EC30-10SLC1-01). ► Pack of 20 keys 	






Headset/Audio Accessories


Part Number	Picture	Description	Notes	Required Items
HDST-35MM-PTT1-01		PTT and VoIP Headset (3.5mm Standard jack)	<ul style="list-style-type: none"> ► For Push-To-Talk (PTT) and VoIP telephony ► Uses standard 3.5mm jack. ► Rotating earpiece allows for right or left ear configuration ► Built-in cord wrap ► mono with microphone ► includes clip for attaching PTT button to clothing. 	
HDST-35MM-PTVP-01		PTT Headset (3.5mm Locking jack)	<ul style="list-style-type: none"> ► For Push-To-Talk (PTT) applications ► Uses 3.5mm rugged jack that is keyed/collared for a locking failsafe connection. ► Rotating earpiece allows for right or left ear configuration ► Built-in cord wrap ► mono with microphone ► includes clip for attaching PTT button to clothing. 	3.5mm Keyed/Collared Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST35-01)

HDST-25MM-PTVP-01		PTT Headset (2.5mm jack)	<ul style="list-style-type: none"> ► For Push-To-Talk (PTT) applications ► 2.5 mm jack ► Rotating earpiece allows for right or left ear configuration ► Built-in cord wrap ► mono with microphone ► includes clip for attaching PTT button to clothing. ► Recommend using 3.5mm headset (HDST-35MM-PTVP-01) instead since this feature provides a more secure locking jack connector. 	2.5mm Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST25-01)
SL+1W-3.5WA (3rd party) * https://workforceaudio.com		Workforce Audio SnapLock PTT Adapter Cable	<ul style="list-style-type: none"> ► For Push-To-Talk (PTT) applications ► 3.5 mm jack ► Adapter cable provide SnapLock connector which accepts a variety of Workforce Audio's earpieces. ► includes clip for attaching PTT button to clothing 	Requires purchase of earpiece for connecting to cable.
See HS2100-HS3100 Accessories Document		HS2100 Rugged Wired Headset	<ul style="list-style-type: none"> ► Built to handle the everyday inevitable drops ► Dustproof, sprayproof and waterproof ► Ready for the freezer and outdoor subzero temperatures ► Feather-light for extraordinary comfort ► Noise cancellation for a superior voice experience in the noisiest environments ► Detachable swivel boom minimizes costs. ► Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. ► User-replaceable pads and windscreens maximize comfort and hygiene 	3.5mm Keyed/Collared Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST35-01) and HS2100 to 3.5mm Standard Cable (CBL-HS2100-3MS1-01) See HS2100/HS3100 Accessories Document for additional headset accessories
VR12 (3rd party) * http://www.blueparrott.com		BlueParrott VR12 Wired Noise Cancelling Headset	<ul style="list-style-type: none"> ► Audio accuracy for voice picking and other speech recognition applications. ► High quality durability stands up to all day, every-day use. ► Lightweight design is easy and comfortable to wear all day. ► Compatible with most major wearable computers and devices used in voice-picking environments. ► G type (GN Netcom) Quick Disconnect. ► Convertible design gives choice of over-the-head and behind-the-neck wearing styles. 	For 3.5mm locking jack (recommended): 3.5mm Keyed/Collared Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST35-01) AND RCH50/RCH51 Quick Disconnect Headset Adapter Cable (ADP-35M-QDCBL1-01) For 2.5mm jack: 2.5mm Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST25-01) AND Headset Adapter Cable (25-124387-02R)







See HS2100-HS3100 Accessories Document		HS3100 Rugged Bluetooth Headset	<ul style="list-style-type: none"> ► HD Voice, also known as Wide Band Audio, brings incredible audio clarity ► Built to handle the everyday inevitable drops ► Dustproof, sprayproof and waterproof ► Ready for the freezer and outdoor subzero temperatures ► Feather-light for extraordinary comfort ► Noise cancellation for a superior voice experience in the noisiest environments ► Swap batteries on the fly — without losing the Bluetooth connection ► Split-second tap-to-pair simplicity using NFC. ► Detachable swivel boom minimizes costs. ► Swivelling boom mutes microphone allowing users to prevent voice pick applications from recognizing non-voice pick conversations. ► User-replaceable pads and windscreens maximize comfort and hygiene ► 15 hours of battery power 	See HS2100/HS3100 Accessories Document for headset accessories
various Bluetooth models B550-XT B350-XT C400-XT C300-XT (3rd party) * http://www.blueparrott.com		BlueParrott Bluetooth Headsets	<ul style="list-style-type: none"> ► Various Bluetooth models available with options that include: <ul style="list-style-type: none"> - Blocking out 96% of background noise - Over 24 hours of talk time - NFC Tap to Pair capable - Bluetooth wireless range capable up to 300 ft. - Convertible wearing options: over the head, behind the neck. See BlueParrot site for model specific options.	
APTT1 (3rd party) * https://www.aina-wireless.com/		Aina Push-To-Talk (PTT) Bluetooth Voice Responder Remote Speaker/Mic (RSM)	<ul style="list-style-type: none"> ► Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ► Includes clip for attaching device to clothing for lapel speaker/mic usage. ► Features several buttons which the application developers can assign to different functions. ► Users can remotely control functions such as push-to-talk, phone calls, channel switching and emergency alerts. ► Device is ruggedized, MIL-STD 810G and IP67. ► Long lasting battery designed for 24 hour approx battery life. Can be recharged via micro-USB port. ► Includes 3.5mm headset jack allowing headphones to be connected for keeping conversations more private. ► Can be easily paired to mobile computer using NFC tap-to-pair. 	


<p>H3-B-1 (3rd party) *</p> <p>https://www.dellking.com</p>		<p>Wandfu H3 Push-To-Talk (PTT) Bluetooth Remote Speaker/Mic (RSM)</p>	<ul style="list-style-type: none"> ▶ Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶ Includes clip for attaching device to clothing for lapel speaker/mic usage. ▶ Includes 3.5mm headset jack allowing headphones to be connected for keeping conversations more private. 	
<p>BTR-155 (3rd party) *</p> <p>K551011 (Zebra orderable SKU) ▶ Discontinued 3/2019, now order from Savox</p> <p>https://www.savoxaccessories.com</p>		<p>Savox BTR-155 Bluetooth Remote Speaker/Mic (RSM)</p>	<ul style="list-style-type: none"> ▶ Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶ Includes clip for attaching device to clothing for lapel speaker/mic usage. ▶ Rugged wireless speaker microphone IP55. ▶ Allows cable-free movement ▶ Familiar speaker microphone functions; PTT and volume buttons ▶ Includes 2.5mm headset jack allowing headphones to be connected for keeping conversations more private. ▶ LED status indication ▶ High speaker volume ▶ Includes: <ul style="list-style-type: none"> - Savox RSM - Modular Wired earpiece - Wall Charger - USB Cable - Quick Start Guide - Carrying Strap 	
<p>BTH-101 (3rd party) *</p> <p>https://www.savoxaccessories.com</p>		<p>Savox Push-To-Talk (PTT) Bluetooth Headset</p>	<ul style="list-style-type: none"> ▶ Bluetooth headset designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶ Also operates as standard Bluetooth headset for taking phone calls. ▶ Device is lightweight and ruggedized, IP55. 	

CBL-HS2100-3MS1-01		HS2100 Headset Standard Cable (3.5 mm jack)	<ul style="list-style-type: none"> ▶ 3.5mm barrel jack connector ▶ For use with TC20, TC51/TC56, TC7X, TC8000, or other devices using a 3.5mm barrel jack audio connector ▶ Cable is 43" (1.1 M) long ▶ Rugged cable with rugged connectors that are keyed/collared for a locking failsafe connection. ▶ Includes one clothing clip. Additional clips can be purchased separately. 	3.5mm Keyed/Collared Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST35-01)
25-124387-02R		RCH50/RCH51 Headset Adapter Cable	<ul style="list-style-type: none"> ▶ Connects RCH50/RCH51 headset to devices with standard 3-pole 2.5mm barrel jack connector. ▶ Updated cable minimizes cross talk and intermittency issues. 	2.5mm Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST25-01)
ADP-35M-QDCBL1-01		RCH50/RCH51 Quick Disconnect Headset Adapter Cable	<ul style="list-style-type: none"> ▶ Connects RCH50/RCH51 headset (or headsets with Quick-Disconnect connector) to devices with 3-pole 3.5mm barrel jack connector. ▶ Cable features a rugged keyed/collared jack for a locking failsafe connection. 	3.5mm Keyed/Collared Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST35-01)
CBL-TC51-HDST25-01		2.5mm Female to 3.5mm Male Headset Adapter Cable (2.5mm jack)	<ul style="list-style-type: none"> ▶ Allows headsets with 2.5mm barrel jacks to be used with EC30. ▶ Converts 3.5mm audio jack to a standard 2.5mm barrel jack connector. ▶ Cable is approximately 6 inches long 	
CBL-TC51-HDST35-01		3.5mm Keyed/Collared Female to 3.5mm Male Headset Adapter Cable (3.5mm jack)	<ul style="list-style-type: none"> ▶ Provides a collared/keyed 3.5mm barrel jack connector. ▶ Required for use with some headsets (i.e. HS2100) that use a locking keyed connector on the headset jack. ▶ Cable is approximately 6 inches long ▶ Includes Retention/Anti-Rotation Lock (ADP-LOCK-3.5HT1-01) 	

ADP-LOCK-3.5HT1-01		Spare/Replacement 3.5mm Audio Adapter Retention and Anti-Rotation Lock	<p>► This clip is used with the Keyed/Collared Female to Male Headset Adapter Cable (CBL-TC51-HDST35-01) and keyed headset cables to prevent cable rotation/spinning and also to provide a secure, reliable headset connection.</p> <p>► Clip is normally included with the Keyed/Collared Female to Male Headset Adapter Cable, this is a spare/replacement clip/lock.</p> <p>► NOTE: This is a Spare/Service Parts item. Contact an authorized Zebra reseller to order.</p>	
--------------------	---	--	--	--

Power Cords/Power Supplies

Part Number	Picture	Description	Notes	Required Items
CBL-DC-388A1-01		DC Power Cord	<p>► Used along with Power Supply PWR-BGA12V50W0WW to power 2-Slot Charge Cradle (CRD-EC30-2SCHG1-01).</p> <p>► Cable length is 1.8 meters</p>	
PWR-BGA12V50W0WW		Power Supply	<p>► Used to power 2-Slot Charge Cradle (CRD-EC30-2SCHG1-01).</p> <p>► 100-240 VAC, 12V, 4.16A, 50W</p> <p>► Provides US DOE Level VI compliance for power efficiency.</p> <p>► Replaces PWRS-14000-148R</p>	DC Line Cord (CBL-DC-388A1-01) and AC Line Cord (23844-00-00R)
CBL-DC-381A1-01		DC Power Cord	<p>► Used to power 10-Slot Cradles when using Level VI Efficiency power supply (PWR-BGA12V108W0WW)</p> <p>► This cable does not include the black extension release latch which is not required when used on Multi-Slot ShareCradles.</p> <p>► CBL-DC-382A1-01 is still typically used though.</p>	
CBL-DC-382A1-01		DC Power Cord	<p>► Used to power 10-Slot Cradles when using Level VI Efficiency power supply (PWR-BGA12V108W0WW)</p> <p>► Cable has black extension tab for releasing the cable from the back of the cradle. This isn't required when using Multi-Slot ShareCradles.</p>	
PWR-BGA12V108W0WW		Power Supply	<p>► Replaces PWRS-14000-241R</p> <p>► Used to power 10-Slot Cradles</p> <p>► 9A, 108W</p> <p>► Level VI Efficiency rated</p>	DC Power Cord (CBL-DC-382A1-01) and AC Line Cord (23844-00-00R)
23844-00-00R		AC Line Cord	<p>► This AC Line Cord is for use in North America. See the AC Line Cords by Country TAG for comparable line cords to use in other countries.</p>	

PWR-WUA5V12W0US (US plug style) PWR-WUA5V12W0GB (UK plug style) PWR-WUA5V12W0EU (EU plug style) PWR-WUA5V12W0AU (Australia plug style) PWR-WUA5V12W0CN (China plug style) PWR-WUA5V12W0IN (India plug style) PWR-WUA5V12W0KR (Korea plug style) PWR-WUA5V12W0BR (Brazil plug style)		USB Power Supply	<ul style="list-style-type: none"> ► Used with USB-C Cable to provide a lower cost charging solution than using a Cradle. ► Provides higher current (2.5A) for faster charging ► 100-240 VAC, 5 V, 2.5 A 	USB-C Cable (CBL-TC5X-USBC2A-01 or CBL-TC2X-USBC-01)
--	---	------------------	---	--