

MC3300 Series Technical Accessory Guide



NOTE: This document is only for general reference. Solutions Pathway and related PMBs should be used for product availability, pricing, and final solution selection.

This document and the information contained therein (Information) are Zebra- confidential, and are provided under, and subject to, the confidentiality provision of your PartnerConnect agreement with Zebra. Any public disclosure (via posting on your website or otherwise) of the Information is strictly prohibited and will be considered a violation of your PartnerConnect agreement with Zebra.

* Zebra does not endorse or specifically recommend any third-party products, accessories, or hardware. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE.

Cradles and Charging

Cradles				
Part Number	Picture	Description	Notes	Required Items
CRD-MC33-2SUCHG-01		Single Slot Charge/Communication Cradle	➤ Provides USB support ➤ Supports MC33 terminal and spare battery charging ➤ Will charge spare battery for MC33 or MC32. ➤ Supports fast-charging of MC33 device and MC33 battery: - charges 1X battery from 0-90% in about 2 hours vs. 3 hours for standard charging rate charges High Capacity (5200 maH) battery from 0-90% in about 3.5 hours vs. 5.5 hours for standard charging rate charges Extended Capacity (7000 maH) battery from 0-90% in about 4.5 hours. ► LED notification of spare battery charging status. ► Note: Cradles manufactured after June 2018 will have a larger base/foot print to prevent the cradle from tipping over when using with MC33 series RFID units.	► Power Supply (PWR-BGA12V50W0WW and CBL-DC-388A1-01) ► AC Line Cord (23844-00-00R). ► USB Cable (25-124330-01R) for PC connection
PSCK-MC3300E (3rd party) *		Portsmith Single Slot Ethernet Cradle Kit	► Cradle communicates with the device via USB. No additional drivers are required. ► Connects to the LAN via a 10/100 mbps Ethernet connection. ► Cradle accommodates terminals equipped with standard or extended batteries. ► Kit includes: cradle, Ethernet cable, Power Supply, and AC Cord.	

EMC Product Line - MC33 TAG Page 1 of 23 Document Update date: 11/18/20

CRD-MC33-5SCHG-01	5-Slot Charge-Only ShareCradle	 ▶ Will charge up to five MC33 units. ▶ Does not charge spare batteries. ▶ Supports fast-charging of MC33: charges 1X battery from 0-90% in about 2 hours vs. 3 hours for standard charging rate. charges High Capacity (5200 maH) battery from 0-90% in about 3.5 hours vs. 5.5 hours for standard charging rate. charges Extended Capacity (7000 maH) battery from 0-90% in about 4.5 hours. ▶ Can be racked/ mounted in a standard 19inch rack system via the mounting accessory (BRKT-SCRD-SMRK-01) 	►DC Line Cord (CBL-DC-381A1-01) and Power Supply (PWR-BGA12V108W0WW) ►AC Line Cord (23844-00-00F
CRD-MC33-4SC4BC-01	5-Slot Charge-Only ShareCradle with Spare Battery Charger	▶ Will charge up to four MC33 terminals and four MC33 or MC32 spare batteries. ▶ Supports fast-charging of MC33 devices and MC33 batteries: - charges 1X battery from 0-90% in about 2 hours vs. 3 hours for standard charging rate charges High Capacity (5200 maH) battery from 0-90% in about 3.5 hours vs. 5.5 hours for standard charging rate charges Extended Capacity (7000 maH) battery from 0-90% in about 4.5 hours. ▶ Can be racked/ mounted in a standard 19inch rack system via the mounting accessory (BRKT-SCRD-SMRK-01)	►DC Line Cord (CBL-DC- 381A1-01) and Power Supply (PWR-BGA12V108W0WW) ►AC Line Cord (23844-00-00F
CRD-MC33-5SETH-01	5-Slot Ethernet/Charging ShareCradle	Allows network speeds up to 1 Gb Will charge up to five MC33 units. Supports fast-charging of MC33: - charges 1X battery from 0-90% in about 2 hours vs. 3 hours for standard charging rate. - charges High Capacity (5200 maH) battery from 0-90% in about 3.5 hours vs. 5.5 hours for standard charging rate. - charges Extended Capacity (7000 maH) battery from 0-90% in about 4.5 hours. ▶ Can be racked/ mounted in a standard 19 inch rack system via the mounting accessory (BRKT-SCRD-SMRK-01)	►DC Line Cord (CBL-DC-381A1-01) and Power Supply (PWR-BGA12V108W0WW) ►AC Line Cord (23844-00-00F
CRD-MC33-4SE4BC-01	MC33 5-Slot Ethemet/Charging ShareCradle with Spare Battery Charger	► Allows network speeds up to 1 Gb ► Will charge up to four MC33 terminals and four MC33 or MC32 spare batteries. ► Supports fast-charging of MC33 devices and MC33 batteries: - charges 1X battery from 0-90% in about 2 hours vs. 3 hours for standard charging rate. - charges High Capacity (5200 maH) battery from 0-90% in about 3.5 hours vs. 5.5 hours for standard charging rate. - charges Extended Capacity (7000 maH) battery from 0-90% in about 4.5 hours. ► Can be racked/ mounted in a standard 19 inch rack system via the mounting accessory (BRKT-SCRD-SMRK-01)	►DC Line Cord (CBL-DC- 381A1-01) and Power Supply (PWR-BGA12V108W0WW) ►AC Line Cord (23844-00-00F

			MC30/MC31/MC32 Single Slot and Multi-Slot Cradles ►NOTE: Adapter Cup does not provide	
ADP-MC33-CRDCUP-01		MC33 Adapter Cup to MC30/MC31/MC32 Legacy Cradles	 Not 1E: Adapter Cup does not provide communications support (USB, Serial, Ethernet). Will only provide charging support. ▶ Does NOT support fast-charging of MC33. MC33 used in legacy cradles will be charged at standard rate: charges 1X battery from 0-90% in about 3 hours at standard charging rate. charges 2X battery from 0-90% in about 5.5 hours at standard charging rate. ▶ Order one Adapter Cup for Single Slo Cradles and four Adapter Cups for Multi-Slot Cradles. 	
BRKT-SCRD-SMRK-01		5-Slot ShareCradle Mounting Bracket	▶ Allows for rack and wall mounting of one 5-Slot ShareCradle, up to four Single Slot ShareCradles, or up to four MC32/MC33 4-Slot Battery Chargers. ▶ Bracket can be mounted on standard 19" network rack or on a wall. ▶ Has cable routing slots and removable power supply tray that stores and conceals power supplies. ▶ Adjustable tabs & screw mounts for easy hanging/installation. ▶ Adjustable orientations: - 25° High Density (5-Slot Charge Only Cradle) - Horizontal (Single Slot Cradle or 4-Slot Battery Chargers). ▶ See the Bluetooth-Generic Accessories TAG for info on 3rd party Network Racks that can be used for mounting this bracket.	
ADP-TC7X-PLT-FX		5-Slot ShareCradle Mounting Bracket Adapter Plate for Honeywell	► Allows Zebra Multi-Slot ShareCradles to be mounted on legacy Honeywell Flex Cradle Wall Mount Brackets (HON SKU #203-641-002). ► Includes hardware to attach plate to HON wall bracket and secure ShareCradle to plate. ► NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this cable.	
Battery Charging				
Part Number	Picture	Description	Notes	Required Items

EMC Product Line - MC33 TAG Page 3 of 23 Document Update date: 11/18/20

SAC-MC33-4SCHG-01		MC32/MC33 4-Slot Battery Charger	➤ This cradle charges spare batteries only (1X/Standard or 2X/Extended size). ➤ Supports charging of both MC33 and MC32 batteries. ➤ Supports fast-charging of MC33 batteries: - charges 1X battery from 0-90% in about 2 hours vs. 3 hours for standard charging rate. - charges High Capacity (5200 maH) battery from 0-90% in about 3.5 hours vs. 5.5 hours for standard charging rate. - charges Extended Capacity (7000 maH) battery from 0-90% in about 4.5 hours. ➤ Can be used standalone or up to four chargers can be installed on Multi-Slot Wall/Rack Mount Bracket (BRKT-SCRD-SMRK-01).	► AC Line Cord (23844-00-00R) To power two sets of 4-slot. Chargers from one power. supply: ► Power Supply (PWR-BGA12V108W0WW) ► DC Y-Cable Line Cord (CBL-DC-523A1-01) ► AC Line Cord (23844-00-00R) To power five 4-slot Chargers: Use MC33 20-Slot Battery
SAC-MC33-20SCHG-01		MC32/MC33 20-Slot Battery Charger	 ▶ Charges MC33 or MC32 spare batteries (1X/Standard or 2X/Extended size). ▶ Uses 5-Slot ShareCradle with five 4-Slot Battery Chargers (SAC-MC33-4SCHG-01) attached. ▶ Does NOT support fast-charging of MC33 batteries. All battery types charged at standard rate: charges 1X battery from 0-90% in about 3 hours at standard charging rate. charges High Capacity (5200 maH) battery from 0-90% in about 3.5 hours vs. 5.5 hours for standard charging rate. charges Extended Capacity (7000 maH) battery from 0-90% in about 4.5 hours. ▶ Can be racked/mounted in a standard 19 inch rack system via the mounting accessory (BRKT-SCRD-SMRK-01). 	381A1-01) ► AC Line Cord (23844-00- 00R)
Direct to Device Charging				
Part Number	Picture	Description	Notes	Required Items
CBL-MC33-USBCHG-01		MC33 USB Communication/Charging Cable		For charging: ▶ USB charger Indoor use: order Country Specific version of USB Power Supply (PWR-WUA5V12W0xx) In Vehicle use: USB Cigarette Lighter Adapter (CHG-AUTO-USB1-01)
Communication Cables				
Part Number	Picture	Description	Notes	Required Items

CBL-MC33-USBCHG-01		MC33 USB Communication/Charging Cable		For charging: ▶ USB charger Indoor use: order Country Specific version of USB Power Supply (PWR-WUA5V12W0xx) In Vehicle use: USB Cigarette Lighter Adapter (CHG-AUTO-USB1-01)
25-124330-01R		MC33 USB Single-Slot Cradle to PC/Host cable	► Used with the Single Slot Cradle (CRE MC33-2SUCHG-01) ► Micro USB connection on cradle end	
PSAK-UCE (3rd party) * http://www.portsmith.com		Portsmith USB Ethernet Adapter Kit for MC30/MC31/MC32 and MC3300 series	▶ Connects to MC3x00 via Single Slot USB cradles. Acts as USB Peripheral device to MC3x00 (USB host) ▶ Requires no separate power supply, has grounded wiring from both the USB and Ethernet ports, and operates on very low power draw directly from the USB connection. ▶ Molded end caps enable the adapter to be aligned side by side or top to bottom, for efficient use of desktop space and organization of cables. ▶ Kit includes PSA1U1E adapter and three USB cables for connecting to a variety of devices. ▶ Android devices require no additional drivers. Windows devices may require software driver from http://www.portsmith.com	For MC31/MC32 Single Slot Charge/Communication Cradle (CRD3000-1000RR)
Snap-On Accessories	.		.	
3PTY-TIS-MC33TGHD	Picture	Pistol Grip Trigger Handle for MC33 Straight-Shooter	P Allows MC33 Straight-Shooter configurations to be used as a gun handle device. ▶ Simple compact trigger handle. Trigger handle mechanically presses the left trigger button on the MC33 when the trigger handle is pulled. ▶ Sides into position on the MC33 and locks into place using the handstrap tether point on the MC33. ▶ MC33 can be recharged in the cradle with the trigger handle on. ▶ Does not block access to camera on back of MC33, which allows for a gun handled camera-enabled device. The MC33 should not be held using the trigger handle while taking pictures to avoid getting user's hand in the shot. ▶ MC33 battery can be swapped without removing the trigger handle. ▶ IP-67 rated, surviving multiple drops on concrete (drop height: 5.9 // 1.8 m) and offering a wide operating temperature range (5°F to 122°F/-15°C to +50°C). ▶ Trigger mechanism was designed for over 1 million pulls. ▶ MC33 Handstrap must be removed to use Trigger Handle. ▶ Only compatible with MC33 Straight-Shooter configurations. ▶ NOTE: This is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.	

EMC Product Line - MC33 TAG Page 5 of 23 Document Update date: 11/18/20

Soft Goods - Cases/Ho	Soft Goods - Cases/Holsters				
Part Number	Picture	Description	Notes	Required Items	
SG-MC33-RDHLST-01		MC33 Rigid Holster	 ▶ This carrying case secures the device to a belt. ▶ Not compatible with MC33 series RFIE units. ▶ Not compatible with devices having Rubber Boot installed. 		
SG-MC3X-SHLSTB-01		Fabric Holster for Brick/Straight-Shooter or Rotating Head configurations	➤ This carrying case secures the MC3x00 to a belt (using belt clip) or can be worn cross-body (using included strap). ➤ Compatible with all Brick/Straight Shooter or Rotating Head units. ➤ Devices with Rubber Boot installed will fit into Holster. The fit will be tight though. ➤ Uses modified strap to secure device in holster vs.11-69293-01R.		
SG-MC3021212-01R		Fabric Holster for Gun configuration	▶ Includes modification with a softer bel loop and stronger button snap to avoid the button from snapping open when the MC3x00 is inserted into the holster. ▶ Devices with Rubber Boot (11-72959-04R) will fit into Holster. The fit will be tight though. ▶ MC33 series RFID units must be inserted into cradle with bottom of device inserted first. ▶ Can be mounted on belt or includes tether points to be used with Universal Should Strap (58-40000-007R)		
O4925DWSPOS2 (3rd party) *		Replacement Swivel Belt Clips for holsters ZEBRA Validated			
11-08062-02R		Belt for holster	► Belt is 2 inches wide ► Extends to 48 inches ► Has improved buckle and softer belt material		
V6198DW (3rd party) * http://www.ultimacase.com	E	Belt Extender	► Used to extend the holster belt (11- 08062-02R) an additional 10 inches		

58-40000-007R		Universal Shoulder Strap	▶1.5" wide, 22 to 50" max. length	
A1236ST (3rd party) * https://www.shilpitrading.com	M	Universal Shoulder Strap	► Belt is 1 inch wide ► Extends to 54 inches ► Moulded shoulder pad ► Plastic swivel snap hooks	
SG-MC33-HDSTPG-01		MC33 Gun Handstrap (single)	► This hand strap is included with MC3300 Gun units but is not included with MC3300x Gun units. ► Optional hand strap for MC3300x Gur units (does not ship with device). ► Replacement hand strap for MC3300 Gun units (ships with device).	
SG-MC32-HDSTG-01 (pack of 3)		Replacement MC31/MC32/MC33 Gun Handstraps	▶This is an alternative lower cost hand strap for Gun units. ▶Lower profile strap does not include UHF RFID tag for asset tracking.	
SG-MC3123342-01R (pack of 5)		MC31/MC32/MC33 Gun Handstrap	▶This is an alternative strap for the MC31/MC32/MC33 Gun for customers that don't want a full handstrap that connects from the battery door or bottom of device to the gun handle.	

SG-MC33-HDSTPB-01	Replacement MC33 Brick or Turret Head Handstrap	►This is the same strap that ships with the MC3300 and MC3300x Brick (straight shooter) or Turret Head units. ►Includes loop for storing optional stylus.	
SG-MC33-LNYDB-01	Lanyard for MC3300 Brick style units	► Allows MC32 or MC3300 Brick/Straigh Shooter or Turret Head units to be attached to a retractable lanyard. ► Lanyard can be worn cross-body using included strap or strap can be removed and lanyard can be attached to belt. ► Standard handstrap must be removed to allow lanyard to be attached to MC3X unit. ► When using as belt mounted lanyard, can be used with Belt for Holster (11-08062-02R) ► Only compatible with MC3300 Brick style devices. Not compatible with MC3300x Brick devices due to the potential of increased WiFi radio output exceeding SAR limit. ► NOT compatible with Gun configuration devices.	

SG-MC33-RBTS-01	Rubber Boot for MC33 Brick/Straight-Shooter units	► Works with Imager configuration brick/straight-shooter units ► Does not increase drop spec of device. Designed to protect the device from the everyday nicks and dings. ► Compatible with fabric holsters. ► Not compatible with Forklift Holder ► Boot must be removed before inserting into cradles.	
SG-MC33-RBTRD-01	Boot for MC33 Turret Head Scanner	➤ Works with Turret Head Scanner configuration units. ➤ Includes Boot for unit. ➤ Does not increase drop spec of device. Designed to protect the device from the everyday nicks and dings. ➤ Compatible with fabric holsters. ➤ Not compatible with Forklift Holder ➤ Boot must be removed before inserting into cradles.	Typically ordered with Cup for Turret Head Scanner (SG- MC33-RBTRT-01)
SG-MC33-RBTRT-01	Cup for MC33 Turret Head Scanner	▶ Does not increase drop spec of device. Designed to protect the device from the everyday nicks and dings.	Typically ordered with Boot for Turret Head Scanner (SG- MC33-RBTRD-01)
SG-MC33-RBTG-01	Rubber Boot for MC33 Gun	➤ Works with both Laser and Imager gun units	

Powered Cradles and Hold				
Powered Cradles and Holders (provides device charging and/or communication)				
Vehicle/Forklift Cradles and Holders				
http://logisterra.com/products		Additional Holsters for MC3000 series		
0000-0543 (3rd party) * _http://www.multiplexx.com/		Hip holster with belt for MC3X Brick/Straight-Shooter units	► Left-hand/right-hand interchangeable ► The holster and belt provide protection and hands free mobility to sensitive equipment	
(3rd party) * http://www.ultimacase.com	Agora Leather website	Additional holsters for MC3000 series		
SG-MC33-RBTG-03		Half Rubber Boot for MC33 series RFID unit	➤ Only compatible with MC33 series RFID units. ➤ Includes holder for optional stylus (SG TC7X-STYLUS-03), which is not included, and tether point for stylus tether. ➤ Does not increase drop spec of device. Designed to protect the device from the everyday nicks and dings. ➤ Devices with Boot will also fit into Fabric Gun Holster (SG-MC3021212-01R) - bottom of MC33 RFID device will insert into holster. The fit will be tight though. ➤ Not compatible with Forklift Holder ➤ Boot covers top half of device allowing easy insertion into cradles.	
SG-MC33-RBTG-02		Rubber Boot for MC33 series RFID unit	▶ Only compatible with MC33 series RFID units. ▶ Includes holder for optional stylus (SGTC7X-STYLUS-03), which is not included, and tether point for stylus tether. ▶ Does not increase drop spec of device. Designed to protect the device from the everyday nicks and dings. ▶ Devices with Boot will also fit into Fabric Gun Holster (SG-MC3021212-01R) - bottom of MC33 RFID device will insert into holster. The fit will be tight though. ▶ Not compatible with Forklift Holder ▶ Boot must be removed before inserting into cradles.	

various (3rd party)* Proclip Charge-Only Cradles/Holders for MC33 series RFID unit Proclip Charge-Only Cradles/Holders for MC33 series RFID unit Mount on vehicle using Proclip Pedestal or Forklift Mount - see Proclip website fork lifts). Holds MC33 series RFID units only Fixed Mount - does not tilt or swivel Mount - see Proclip website Mount ready via AMPS hole pattern http://www.proclipusa.com/category/zebra Un-Powered Cradles and Holders (passive holders, no charging support)	various (3rd party) * http://www.proclipusa.com/category/zebra	Proclip Charge-Only Cradles/Holders	device in place during intense	Mount on vehicle using ProClip Pedestal or Forklift Mount - see ProClip website
	(3rd party) * http://www.proclipusa.com/category/zebra	Cradles/Holders for MC33 series RFID unit	 powered - hard-wired Also available with: Top support arm. Top support arm with vibration dampers to protect device when mounting on higher vibration vehicles (i.e. fork lifts). Holds MC33 series RFID units only. Fixed Mount - does not tilt or swivel 	ProClip Pedestal or Forklift
Part Number Picture Description Notes Required Items	Part Number Picture	arging support) Description	Notes	Required Items

MNT-MC33-FLCHKT-01		Fork Lift Cradle Kit (un-powered)	▶ Bracket holds all MC3X00 configurations, except RFID units, for convenient mounting on fork lift. ▶ Installs on a roll bar or square surface of the forklift and allows the device to be used in landscape or portrait mode. ▶ Includes RAM 1" diameter ball on back of cradle. ▶ Does NOT charge MC3X00. ▶ Kit includes Fork Lift Cradle (MNT-MC33-FLCH-01), RAM Mount Arm (MNT-RAM-B201U), and RAM Mount Base (MNT-RAM-B247U25)	
MNT-MC33-FLCH-01		Fork Lift Cradle (un-powered)	▶ Bracket holds all MC3X00 configurations, except RFID units, for convenient mounting on fork lift. ▶ Installs on a roll bar or square surface of the forklift and allows the device to be used in landscape or portrait mode. ▶ Includes RAM 1" diameter ball on back of cradle. ▶ Does NOT charge MC3X00. ▶ Not compatible with devices with rubber boot attached.	►RAM Mount Arm for Fork Lift Cradle (MNT-RAM-B201U) ►RAM Mount Base for Fork Lif Cradle (MNT-RAM-B247U25)
MNT-RAM-B201U	RAM	RAM Mount Arm for MC3X00 Fork Lift Cradle	► Used with Fork Lift Cradle (MNT-MC33 FLCH-01) ► RAM Double Sock Arm for 1" ball ► Uses RAM Mount P/N RAM-B-201U	
MNT-RAM-B247U25		RAM Mount Base for MC3X00 Fork Lift Cradle	► Used with Fork Lift Cradle (MNT-MC33 FLCH-01) ► Attaches to square shaped rail/post o forklift. ► 2.5" Max Width Square Rail Base with 1" diameter ball ► Uses RAM Mount P/N RAM-B-247U-25	

<u> </u>			
	ProClip MC33 Holder, Rear Facing Display, Top Hold, No Tilt or Swivel (un-powered)	► Holds MC33 Gun, Brick, or Turret Head devices ► Not compatible with MC33 series RFID units. ► Rear Facing - Device screen faces away from user to prevent device usage while driving ► Fixed Mount - does not tilt or swivel ► Mount ready via AMPS hole pattern	Mount on vehicle using ProClip Pedestal or Forklift Mount - see ProClip website
(3rd party) *	ProClip MC33 Holder, Rear Facing Display, Top Hold, with Tilt Swivel (un-powered)	➤ Holds MC33 Gun configurations only. ➤ Not compatible with MC33 series RFID units. ➤ Rear Facing - Device screen faces away from user to prevent device usage while driving ➤ Variable Mount - can be tilted and swiveled and mounted vertically or horizontally. ➤ Mount ready via AMPS hole pattern	Mount on vehicle using ProClip Pedestal or Forklift Mount - see ProClip website
	ProClip MC33 Holder, Front Facing Display, Top Hold, No Tilt or Swivel (un-powered)	► Holds MC33 Gun, Brick, or Turret Head devices. ► Not compatible with MC33 series RFID units. ► Front Facing - allows user to access screen and keyboard while cradled. ► Fixed Mount - does not tilt or swivel ► Mount ready via AMPS hole pattern	Mount on vehicle using ProClip Pedestal or Forklift Mount - see ProClip website

711040 (3rd party) * http://www.proclipusa.com/category/zebra	ProClip MC33 Holder, Front Facing Display, Top Hold, with Tilt Swivel (un-powered)	► Holds MC33 Gun, Brick, or Turret Head devices. ► Not compatible with MC33 series RFID units. ► Front Facing - allows user to access screen and keyboard while cradled. ► Variable Mount - can be tilted and swiveled. ► Mount ready via AMPS hole pattern.	Mount on vehicle using ProClip Pedestal or Forklift Mount - see ProClip website
	ProClip MC33R RFID Holder, Front Facing Display, Top Hold, No Tilt or Swivel (un-powered)	► Holds MC33 series RFID devices. ► Front Facing - allows user to access screen and keyboard while cradled. ► Fixed Mount - does not tilt or swivel ► Mount ready via AMPS hole pattern	Mount on vehicle using ProClip Pedestal or Forklift Mount - see ProClip website
	ProClip MC33R RFID Holder with Vibration Dampers, Front Facing Display, Top Hold, No Tilt or Swivel (un-powered)	➤ Holds MC33 series RFID devices. ➤ Front Facing - allows user to access screen and keyboard while cradled. ➤ Fixed Mount - does not tilt or swivel ➤ Vibration Dampers protect device when mounting on higher vibration vehicles (i.e. fork lifts). ➤ Mount ready via AMPS hole pattern	Mount on vehicle using ProClip Pedestal or Forklift Mount - see ProClip website

7160-0854 (3rd party) *	com	Gamber-Johnson Barcode Scanner/Mobile Computer Mount	► Attaches to the overhead guard leg on forklift trucks. It is designed to fit rectangular pillars between 1.5" to 2.5" wide with easy installation ► Heavy gauge steel construction for long-term durability in a rugged environment. ► Black powdercoat finish for maximum corrosion resistance. ► Designed to securely fit most handheld barcode scanners and mobile computers. ► Works with wireless and wired devices	
7160-1306 (3rd party) *	com	Gamber-Johnson Scanner Pocket Mount with Small Back Plate	▶ Scanner mount is designed to support scanner or handheld computer in a rugged environment by holding it securely to the overhead guard leg of fork lift vehicle. ▶ Adjustable in width, and offers 3 mounting orientations from the overhead guard leg or one of Gamber-Johnson's extension bars. ▶ Designed to hold most handheld computers and scanners. ▶ Adjustable to fit 3.5" to 4.5" width and set at 2.5" tall ▶ Designed to be orientated inside, outside, or inline with the overhead guard leg. ▶ Attaches to rectangular overhead guard legs that are 1.5 in to 2.5 in (3.81 cm to 6.35 cm) wide.	
AA1036DW (3rd party) *		MC3XXX-G (Gun) Forklift Holster	► Includes cable ties for mounting holster to forklift ► Does not provide device charging	
Misc				
Part Number	Picture	Description	Notes	Required Items
SG-TC7X-STYLUS-03 (pack of 3) SG-TC7X-STYLUS-06 (pack of 6) NOTE: 6-pack is a custom product. Please work with your Zebra representative to open a Custom Product Request (CPR) if you would like to order this item.		Stylus Kit with Tether	▶ Includes fine-pitch, capacitive Stylus (SG-TC7X-STYLUS1-03) and coiled tether (KT-TC7X-TETHR1-03) ▶ Conductive Carbon-filled plastic material w/ 5mm tip. ▶ Length of stylus is 3.5". ▶ Rigid plastic stylus is optimized for enterprise durability. ▶ Clip & tether point to reduce loss. Tether to Handstrap ▶ When not being used stylus can be stored in loop on Handstrap or in the optional Holster	

			I	1
SG-STYLUS-TCX-MTL-03 (pack of 3)		Fiber Tipped Stylus	▶ Black Passive Stylus with Zebra logo ▶ 5" length ▶ Heavy duty - made from stainless steel and brass. No plastic parts - real pen feel. ▶ Can be used in rain. ▶ Micro-Knit Hybrid Mesh Fiber Tip provides silent, smooth gliding use. ▶ Big improvement over rubber tipped o plastic tipped stylus. ▶ Compatible with all capacitive touch screen devices. ▶ Can be tethered to device using KT- TC7X-TETHR1-03 or SG-ET5X- SLTETR-01.	
KT-TC7X-TETHR1-03 (pack of 3)		Replacement Coiled Tether for Stylus	► This tether is included with Stylus Kit with Tether (SG-TC7X-STYLUS-03)	
SG-ET5X-SLTETR-01 (single)		Replacement Coiled Tether for Stylus	►This tether is typically used with the ET5X series' stylus but can be used with MC33 Stylus.	
MISC-MC33-SCRN-01 (pack of 5)		MC33 Tempered Glass Screen Protector (pack of 5)	▶Tempered glass ▶Includes alcohol wipes, cleaning cloth and tools needed for screen protector installation.	
Additional Screen Protectors (3rd party) * http://www.nushield.com		Additional Screen Protectors	NuShield AG™ - works well indoors under bright lights to minimize glare. NuShield AM™ - antimicrobial film is an antiglare film designed for hospitals, public kiosks, restaurants and POS terminals where transmission of disease is a primary concern. NuShield DayVue™ - antireflective film is the best choice for displays that are being used outdoors.	
Headset/Audio Access	ories			
Part Number	Picture	Description	Notes	Required Items

HS2100-OTH	HS2100 Rugged Wired Headset (Over the Head headband)	Built to handle the everyday inevitable drops Dustproof, sprayproof and waterproof Ready for the freezer and outdoor subzero temperatures Feather-light for extraordinary comfort Noise cancellation for a superior voice experience in the noisiest environments Detachable swivel boom minimizes costs. Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. User-replaceable pads and windscreens maximize comfort and hygiene. Not compatible with MC33 series RFID units or MC3300x units which do not have a headset jack.	Quick Disconnect Headset cable (CBL-HS2100-QDC1-02) AND MC31/MC32 to Quick Disconnect Adapter Cable (25- 124411-02R)
HS2100-BTN-L	HS2100 Rugged Wired Headset (Behind the Neck Left headband)	▶ Built to handle the everyday inevitable drops ▶ Dustproof, sprayproof and waterproof ▶ Ready for the freezer and outdoor subzero temperatures ▶ Feather-light for extraordinary comfort ▶ Noise cancellation for a superior voice experience in the noisiest environments ▶ Detachable swivel boom minimizes costs. ▶ Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. ▶ User-replaceable pads and windscreens maximize comfort and hygiene. ▶ Not compatible with MC33 series RFID units or MC3300x units which do not have a headset jack.	Quick Disconnect Headset cable (CBL-HS2100-QDC1-01) AND MC31/MC32 to Quick Disconnect Adapter Cable (25- 124411-02R)
VR12 (3rd party) * http://www.blueparrott.com	BlueParrott VR12 Wired Noise Cancelling Headset	▶ Audio accuracy for voice picking and other speech recognition applications. ▶ High quality durability stands up to all-day, every-day use. ▶ Lightweight design is easy and comfortable to wear all day. ▶ Compatible with most major wearable computers and devices used in voice-picking environments. ▶ G type (GN Netcom) Quick Disconnect. ▶ Convertible design gives choice of over-the-head and behind-the-neck wearing styles. ▶ Not compatible with MC33 series RFIE units or MC3300x units which do not have a headset jack.	Headset Adapter Cable (25- 124411-02R)

various Bluetooth models B550-XT B350-XT B350-XT C300-XT C300	See HS2100-HS3100 Accessories Document		HS3100 Rugged Bluetooth Headset	► HD Voice, also known as Wide Band Audio, brings incredible audio clarity ► Built to handle the everyday inevitable drops ► Dustproof, sprayproof and waterproof ► Ready for the freezer and outdoor subzero temperatures ► Feather-light for extraordinary comfort ► Noise cancellation for a superior voice experience in the noisiest environments ► Swap batteries on the fly — without losing the Bluetooth connection ► Split-second tap-to-pair simplicity using NFC. ► Detachable swivel boom minimizes costs. ► Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. ► User-replaceable pads and windscreens maximize comfort and hygiene ► 15 hours of battery power	
designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). Includes clip for attaching device to closthing for lapel speaker/mic usage. Features several buttons which the application developers can assign to different functions. Users can remotely control functions such as push-to-talk, phone calls, channel switching and emergency alerts. Device is ruggedized, MIL-STD 810G and IP67. Long lasting battery designed for 24 hour approx battery life. Can be recharged via micro-USB port. Includes 3.5mm headset jack allowing headphones to be connected for keeping conversations more private. Can be easily paired to mobile	B550-XT B350-XT C400-XT C300-XT (3rd party) *			with options that include: - Blocking out 96% of background noise - Over 24 hours of talk time - NFC Tap to Pair capable - Bluetooth wireless range capable up to 300 ft. - Convertible wearing options: over the head, behind the neck. See BlueParrot site for model specific	
https://www.aina-wireless.com/ computer using NFC tap-to-pair.	(3rd party) *	(C)	Bluetooth Voice Responder	designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶ Includes clip for attaching device to closthing for lapel speaker/mic usage. ▶ Features several buttons which the application developers can assign to different functions. ▶ Users can remotely control functions such as push-to-talk, phone calls, channel switching and emergency alerts. ▶ Device is ruggedized, MIL-STD 810G and IP67. ▶ Long lasting battery designed for 24 hour approx battery life. Can be recharged via micro-USB port. ▶ Includes 3.5mm headset jack allowing headphones to be connected for keeping conversations more private. ▶ Can be easily paired to mobile	

H3-B-1 (3rd party) *	wandfu	Wandfu H3 Push-To-Talk (PTT) Bluetooth Remote Speaker/Mic (RSM)	▶Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶Includes clip for attaching device to closthing for lapel speaker/mic usage. ▶Includes 3.5mm headset jack allowing headphones to be connected for keeping conversations more private.	
BTR-155 (3rd party) * K551011 (Zebra orderable SKU) Discontinued 3/2019, now order from Savox		Savox BTR-155 Bluetooth Remote Speaker/Mic (RSM)	▶ Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶ Includes clip for attaching device to closthing for lapel speaker/mic usage. ▶ Rugged wireless speaker microphone IP55. ▶ Allows cable-free movement ▶ Familiar speaker microphone functions; PTT and volume buttons ▶ Includes 2.5mm headset jack allowing headphones to be connected for keeping conversations more private. ▶ LED status indication ▶ LED status indication ▶ High speaker volume ▶ Includes: - Savox RSM - Modular Wired earpiece - Wall Charger - USB Cable - Quick Start Guide - Carrying Strap	
BTH-101 (3rd party) *		Savox Push-To-Talk (PTT) Bluetooth Headset	▶ Bluetooth headset designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶ Also operates as standard Bluetooth headset for taking phone calls. ▶ Device is lightweight and ruggedized, IP55.	

CBL-HS2100-QDC1-02	O	HS2100 Quick Disconnect Cable	► For use when connecting HS2100 to devices using standard Quick Disconnect jack. ► Cable length is approximately 33" (84 cm). ► Has improved quick disconnect connector and strain relief vs. CBL-HS2100-QDC1-01.		
25-124389-01R	Bannanana	MC31/MC32/MC33 Headset Adapter Cable, bare wire	▶ to be discontinued 2/2021, see PMB 10520 ▶ Cable has right angle connector and locking screw into the MC31/32/33's audio jack. ▶ Bare wire end connector allows other manufacturers to build their own proprietary connectors on the opposite end for connections to other headsets. ▶ Not compatible with MC33 series RFIE units or MC3300x units which do not have a headset jack.		
25-124411-03R		MC31/MC32/MC33 Headset Adapter Cable, HS2100 / RCH50/ BlueParrot connector	➤ Cable has right angle connector and locking screw into the MC33 audio jack. ➤ Connects HS2100, RCH50, BlueParrot, Voxware, and Eartec headsets ➤ Updated cable minimizes cross talk and intermittency issues. ➤ Not compatible with MC33 series RFIE units or MC3300x units which do not have a headset jack.		
Power Cords/Power Supplies					
Part Number	Picture	Description	Notes	Required Items	
Part Number CBL-DC-388A1-01	Picture	Description DC Power Cord	Notes ▶ Used along with Power Supply PWR-BGA12V50W0WW to power Single Slot Cradle, MC32/MC33 4-Slot Battery Charger. ▶ Cable length is 1.8 meters		
	Picture		► Used along with Power Supply PWR-BGA12V50W0WW to power Single Slot Cradle, MC32/MC33 4-Slot Battery Charger.		
CBL-DC-388A1-01		DC Power Cord	 ▶ Used along with Power Supply PWR-BGA12V50W0WW to power Single Slot Cradle, MC32/MC33 4-Slot Battery Charger. ▶ Cable length is 1.8 meters ▶ Used to power Single Slot Cradles, MC32/MC33 4-Slot Battery Charger. ▶ 100-240 VAC,12V, 4.16A, 50W ▶ Provides US DOE Level VI compliance for power efficiency. 	DC Line Cord (CBL-DC-388A1-01) and AC Line Cord (23844-	

CBL-DC-382A1-01		DC Power Cord	► Used with Power Supply PWR-BGA12V108W0WW to power 4-Slot MC30/MC31/MC32 Legacy Cradles.	
CBL-DC-523A1-01	10	2-Way DC Y Power Cord	► Used to power two 4-Slot Battery Chargers with one Power Supply (PWR- BGA12V108W0WW)	
PWR-BGA12V108W0WW	Total Control of the	Power Supply	► Used to power 5-Slot Cradles, and 20 Slot MC33 Spare Battery Charger. ► 100-240 VAC, 12V, 9A, 108W ► Provides US DOE Level VI compliance for power efficiency. ► Replaces PWRS-14000-241R	CBL-DC-381A1-01 and 23844- 00-00R
23844-00-00R		AC Line Cord	►This AC Line Cord is for use in North America. See the AC Line Cords by Country TAG for comparable line cords to use in other countries.	
PWR-WUA5V12W0US (US plug style) PWR-WUA5V12W0GB (UK plug style) PWR-WUA5V12W0EU (EU plug style) PWR-WUA5V12W0AU (Australia plug style) PWR-WUA5V12W0CN (China plug style) PWR-WUA5V12W0IN (India plug style) PWR-WUA5V12W0KR (Korea plug style) PWR-WUA5V12W0KR (Korea plug style) PWR-WUA5V12W0BR (Brazil plug style)		USB Power Supply	► Used with MC33 Charge/Communication Cable (CBL-MC33-USBCHG-01) to charge device. ► Provides higher current (2.5A) for faster charging ► 100-240 VAC, 5 V, 2.5 A	
CHG-AUTO-USB1-01 CHG-AUTO-USB1-BR (for Brazil)	CATOR I	USB Cigarette Lighter Adapter	►Can be used to charge MC33 from USB snap-on cable. ►Includes two USB A ports providing higher current (2.5A) for faster charging	
Batteries				
Part Number	Picture	Description	Notes	Required Items

BTRY-MC33-27MA-01 (single) BTRY-MC33-27MA-10 (10 pack) BTRY-MC33-27MA-IN (for use in India)	© Presidents (Control of the control of the contro	MC33 Spare Standard Capacity Battery with PowerPrecision Plus (2740 mAh)	Designed, manufactured & tested to meet rigorous controls & standards ▶ Premium-grade cells with higher capacity & longer life cycle ▶ Designed to help prevent overcharging & electrical shock ▶ Strong & robust housing for optimal performance & durability ▶ Information available: - Advanced state of Charge (shows the remaining battery power based on two factors: present charge and present real-time usage patterns of the device. - Advanced State of Health (highly accurate end-of-life prediction) - Dynamic usage patterns are constantly calculated, factoring in criteria such as the applications that are in use and scanning frequency). ▶ Not compatible with MC33 series RFIE units.	
BTRY-MC33-52MA-01 (single) BTRY-MC33-52MA-10 (10 pack) BTRY-MC33-52MA-IN (for use in India)	The state of the s	MC33 Spare High Capacity Battery with PowerPrecision Plus (5200 mAh)	Designed, manufactured & tested to meet rigorous controls & standards ▶ Premium-grade cells with higher capacity & longer life cycle ▶ Designed to help prevent overcharging & electrical shock ▶ Strong & robust housing for optimal performance & durability ▶ Information available: - Advanced state of Charge (shows the remaining battery power based on two factors: present charge and present real-time usage patterns of the device. - Advanced State of Health (highly accurate end-of-life prediction) - Dynamic usage patterns are constantly calculated, factoring in criteria such as the applications that are in use and scanning frequency).	

EMC Product Line - MC33 TAG Page 22 of 23 Document Update date: 11/18/20

BTRY-MC33-70MA-01 (single) BTRY-MC33-70MA-10 (10 pack) BTRY-MC33-70MA-IN (single, for use in India)	Control of control of the control of	MC33 Spare Extended Capacity Battery with PowerPrecision Plus (7000 mAh) - For MC33 series RFID and MC3300x units	Designed, manufactured & tested to meet rigorous controls & standards ▶ Premium-grade cells with higher capacity & longer life cycle ▶ Designed to help prevent overcharging & electrical shock ▶ Strong & robust housing for optimal performance & durability ▶ Information available: - Advanced state of Charge (shows the remaining battery power based on two factors: present charge and present real-time usage patterns of the device). - Advanced State of Health (highly accurate end-of-life prediction) - Dynamic usage patterns are constantly calculated, factoring in criteria such as the applications that are in use and scanning frequency. ▶ Increases run time of MC33 series RFID unit an additional 1.5 hours vs. using High Capacity 5200 mAh battery. ▶ Only compatible with any MC33 series RFID units or MC3300x units. ▶ Not compatible with MC3300 non-RFID units.	
BTRY-MC32-01-01 BTRY-MC32-01-10 (10 pack)	1X	MC3200 Spare 1X Battery with PowerPrecision (2740 mAH)	 ▶ Works with all MC32XX configurations only ▶ Supports PowerPrecision battery management application ▶ Also compatible with MC3300. ▶ Not compatible with any MC33 series RFID units or MC3300x units. 	
BTRY-MC32-52MA-01 BTRY-MC32-52MA-10 (10 pack)	2X	MC3200 Spare 2X High Capacity Battery with PowerPrecision (5200 mAH)	► Works with MC32xx configurations ► Supports PowerPrecision battery management application ► Also compatible with MC3300 and MC3300 RFID units. ► Not compatible with MC3300x or MC3300x RFID units.	