

MioCARE™ A210-235



Tablet computers designed for healthcare

The MioCARE™ 5.7" and 5.88" touch screen A210 HD and A235 tablets come with WiFi and include integrated NFC plus a 1D/2D barcode scanner* offering data capture built right into your workflow. This gives real-time and context aware reporting and data retrieval offering significant error reduction.

Integrated GPS adds location awareness and the WiFi functionality on the MioCARE™ A210 HD and A235 devices enables connection both indoors and out through use of the fast charging cradles allowing them to be constantly available.



Unified communication

Redundant connectivity with WiFi and Bluetooth® 4.0 connected



Open & flexible

Uses Android[™] 4.2.2/5.1** with SDK and emulator support Multi-touch 5.7" screen



► IP54 sealed

- Robust design
- Water, dust and 1m drop resistant



Integrated data capture

NFC, HF RFID and 1D/2D barcodes built into workflows*

MioCARE™





Specifications	A210 HD	A235
Display	5.7" (HD) TFT colour LCD (720x1280), 450 nits	5.88" WVGA (800x480), 350 nits
ouch Panel	Capacitive multi-touch panel	
latform	TI OMAP4470, 1.5GHz	
S	Android 4.2.2 / Android 5.1**	
1emory	1GB RAM/16GB ROM	
xpansion	MicroSD up to 64GB	
Wireless Interface	NFC, HF RFID	
	Wireless WAN Data	
	Security: IEEE 802.1x, WEP, WPA PSK with TKIP, WPA2 PSK with AES	
	Wireless 802.11 a/b/g/n (2.4 & 5GHz)	
	Bluetooth® 4.0	
	GPS	
Sensors	Accelerometer – auto rotation	
BCR	N/A	2D Code: CR8000
amera	Front: 1.2M FF; Rear 5M AF with flash LED	•
Physical Interface	microSIM card slot	
	microSD slot	
	mini USB-B 2.0	
	32 pogo pins (charging & USB host only), for cradle	
	Build-in mic	
	Build-in speaker	
	Headset jack	
	Power DC-jack	
uttons	Power, volume up/down (volume up enables BCR function)	
Battery	3000 mAH Lithium-Ion battery (rechargeable) - Ba	ttery life up to 6 hours
	LED Indicator	
Environment	IP54 and 1m drop resistant	
	-10°C to 50°C operating temperature	
	-20°C to 60°C storage temperature	
	Humidity: 0~90%, Non-Condense	
	Altitude: Operating: 0~10,000ft (3000m)	
Standard Accessory	Power adapter with power cord (UK, EU)	
	USB to mini USB cable	
Certification	CE/CB, IP54	
Narranty	12 months (extended warranty available)	
Weight	370g	
Dimensions	200x99x15mm	

Available accessories:

* only available on A235

 ${\sf AC\ Mains\ charger;\ Single\ cradle\ inc.\ AC\ power\ pack;\ Multi-unit}$ cradle inc. AC power pack (6); USB Cable; HDMI to mini HDMI or micro HDMI output cable; Hand Lanyard (pack of 5); Protective case; Hand Strap;

