

EC30 Technical Accessory Guide



Document Update date: 9/6/19

NOTE: This document is only for general reference. Solution Builder and related PMBs should be used for product availability, pricing, and final solution selection.

* Zebra does not endorse or specifically recommend any third-party products, accessories, or hardware. ZEBRA DISCLAIMS ANY AND ALL LIABILITY, INCLUDING ANY EXPRESS OR IMPLIED WARRANTIES, WHETHER ORAL OR WRITTEN, FOR SUCH THIRD PARTY PRODUCTS, ACCESSORIES, OR HARDWARE. THE CUSTOMER ACKNOWLEDGES THAT NO REPRESENTATION HAS BEEN MADE BY ZEBRA AS TO THE FITNESS OF THE THIRD-PARTY PRODUCTS, ACCESSORIES, OR HARDWARE FOR THE CUSTOMER'S INTENDED PURPOSE.

Cradles/Charging

Our disc					
Cradles Part Number	Picture	Description	Notes	Required Items	
CRD-EC30-2SCHG1-01	10.00	2-Slot Charge Only Cradle	▶Charges two EC30 units.	Power Supply (PWR-BGA12V50W0WW) →DC Line Cord (CBL-DC-388A1-01) →AC Line Cord (23844-00-00R)	
CRD-EC30-10SC1-01	A SOUTH OF THE PROPERTY OF THE	10-Slot Charge Only Cradle	▶Cradle can be mounted on desktop or can be mounted on 19" rack using optional brackets listed below.	Power Supply (PWR-BGA12V108W0WW) DC Line Cord (CBL-DC-381A1-01) →AC Line Cord (23844-00-00R)	
CRD-EC30-10SLC1-01		10-Slot LOCKING Charge Only Cradle	▶ Cradle can be mounted on desktop or can be mounted on 19" rack using optional brackets listed below. ▶ Release of device from cradle is controlled by the device. Colored green LED light around cradle slot indicates when device is unlocked.	►Power Supply (PWR-BGA12V108W0WW) ►DC Line Cord (CBL-DC-381A1-01) ►AC Line Cord (23844-00-00R)	
BRKT-SCRD-SMRK-01		Multi-Slot Wall/Rack Mount Bracket	*Allows for rack and wall mounting of one 10-Slot Charger. *Bracket can be mounted on standard 19" network rack or on a wall. *Cable routing slots & removable power supply holder tray. *Adjustable tabs & screw mounts for easy hanging/installation. *Adjustable orientations - horizontal, vertical, angled. *See the Bluetooth-Generic Accessories TAG for info on 3rd party Network Racks that can be used for mounting this bracket.		

EMC Product Line - EC30 TAG Page 1 of 15

	_			
BRKT-EC30-10SC1-01		High Density Multi-Slot Wall/Rack Mount Bracket	*Allows for rack and wall mounting of one 10-Slot Charger. *Bracket can be mounted on standard 19" network rack or on a wall. *Bracket will hold cradle in vertical position with device displays facing up, scan engines facing out, to provide for higher density device mounting. *See the Bluetooth-Generic Accessories TAG for info on 3rd party Network Racks that can be used for mounting this bracket.	
Direct to Device Charging				
Part Number	Picture	Description	Notes	Required Items
CBL-TC5X-USBC2A-01		USB-C cable for Charging/Communication	➤USB-A to USB-C cable ➤Attaches to USB-C port on the bottom of the device or to the Single Slot Base Charge-Only Cradle (TBD). ➤Can be used to charge the EC30 via USB connections (PC, USB AC Wall Outlet adapter, USB Cigarette Lighter adapter) ➤Cable length is 1.5M (~5 ft.) ➤Can also be used to communicate with EC30 without using a Cradle.	USB Power Adapter (PWR-WUA5V12W0US - or country specific version)
CBL-TC2X-USBC-01		USB-C cable for Charging/Communication	*USB-A to USB-C cable *Attaches to USB-C port on the bottom of the device or to the Single Slot Base Charge-Only Cradle (TBD). *Can be used to charge the EC30 via USB connections (PC, USB AC Wall Outlet adapter, USB Cigarette Lighter adapter) *Cable length is 1.5M (~5 ft.) *Can also be used to communicate with EC30 without using a Cradle. *NOTE: This cable includes an additional ferrite bead. Use CBL-TC5X- USBC2A-01 for a lower profile cable.	USB Power Adapter (PWR-WUA5V12W0US - or country specific version)
3rd party *		USB-C cable for Charging/Communication	*USB-A to USB-C cable *Attaches to USB-C port on the bottom of the device or to the Single Slot Base Charge-Only Cradle (TBD). *Can be used to charge the EC30 via USB connections (PC, USB AC Wall Outlet adapter, USB Cigarette Lighter adapter) *Cable length is 1.5M (~5 ft.) *Can also be used to communicate with EC30 without using a Cradle.	
Communication Cables				
Part Number	Picture	Description	Notes	Required Items

CBL-TC5X-USBC2A-01		USB-C cable for Charging/Communication	➤USB-A to USB-C cable Attaches to USB-C port on the bottom of the device or to the Single Slot Base Charge-Only Cradle (TBD). ➤Can be used to charge the EC30 via USB connections (PC, USB AC Wall Outlet adapter, USB Cigarette Lighter adapter) ➤Cable length is 1.5M (~5 ft.) ➤Can also be used to communicate with EC30 without using a Cradle.	USB Power Adapter (PWR- WUA5V12W0US - or country specific version)
CBL-TC2X-USBC-01		USB-C cable for Charging/Communication	*USB-A to USB-C cable *Attaches to USB-C port on the bottom of the device or to the Single Slot Base Charge-Only Cradle (TBD). *Can be used to charge the EC30 via USB connections (PC, USB AC Wall Outlet adapter, USB Cigarette Lighter adapter) *Cable length is 1.5M (~5 ft.) *Can also be used to communicate with EC30 without using a Cradle. *NOTE: This cable includes an additional ferrite bead. Use CBL-TC5X- USBC2A-01 for a lower profile cable.	USB Power Adapter (PWR- WUA5V12W0US - or country specific version)
3rd party *		USB-C cable for Charging/Communication	*USB-A to USB-C cable *Attaches to USB-C port on the bottom of the device or to the Single Slot Base Charge-Only Cradle (TBD). *Can be used to charge the EC30 via USB connections (PC, USB AC Wall Outlet adapter, USB Cigarette Lighter adapter) *Cable length is 1.5M (~5 ft.) *Can also be used to communicate with EC30 without using a Cradle.	USB Power Adapter (PWR- WUA5V12W0US - or country specific version)
Soft Goods/Wearables				
Part Number	Picture	Description	Notes	Required Items

SG-EC30-ADP1-01	Accessory Adapter	►Holds the EC30 and is used with a variety of other accessories listed in this section. ►Black color	
SG-EC30-CLIP1-01	Vest/Pocket Lanyard	▶Tether in-pocket accessory uses coiled lanyard attached to Accessory Adapter. ▶Prevents loss and drops of EC30 ▶EC30 can be easily dropped in vest pocket or other garment pocket when not in use. ▶Intuitive pocket clip anchors lanyard ▶Uses Accessory Adapter (SG-EC30-ADP1-01) and clip-on coiled tether.	

SG-EC30-BLYD1-01 (single) SG-EC30-BLYD1-10 (pack of 10)	Basic Neck Lanyard	►Uses Accessory Adapter (SG-EC30-ADP1-01) and Neck Lanyard. ►Black color ►Lanyard has adjustable length and safety break-away. ►Length is adjustable between 16" and 30" •Can be worn in short position around neck or at full length as a satchel.	
SG-EC30-RLYD1-01 (single) SG-EC30-RLYD1-10 (pack of 10)	Retractable Neck Lanyard	►Uses Accessory Adapter (SG-EC30-ADP1-01), Neck Lanyard and Magnetic Retractor (SG-EC30-RET1-01). ►Black color Familiar neck lanyard with unique magnetic "home holding feature" ►Extends to 30" with low pull-back to avoid "sling shot" retracting. ►Secondary clips reduce swinging of device when user bends over or leans forward. ►Lanyard has adjustable length and safety break-away	

SG-EC30-RCB1-01	00:01	Retractable Belt Clip/Carabiner	►Uses Accessory Adapter (SG-EC30-ADP1-01) and Magnetic Retractor (SG-EC30-RET1-01). ►Black color ►Carabiner can be attached to belt loop or other articles of clothing. ►Extends to 30" with low pull-back to avoid "sling shot" retracting.	
SG-EC30-RET1-01		Spare/Replacement Magnetic Retractor		
SG-EC30-ARM1-01 (standard length strap - 12 inches) SG-EC30-ARML1-01 (long strap - 18 inches)		Arm/Wrist Mount	*Allows EC30 to be worn on upper or lower portion of arm. *Only one orientation supported *Very light scanning possible *Provides access to audio jack	

SG-EC30-HLSTR1-01		Soft Holster	►Leather construction with protective flap and belt clip.	
SG-EC30-RHLSTR1-01	10:00	Rigid Holster	►Holster allows EC30 to be worn on belt ►Rotates to be used at any orientation ►EC30 can be inserted in any direction while still allowing access to the audio jack.	
Misc				
Part Number	Picture	Description	Notes	Required Items
SG-EC30-SCRNP1-05 (pack of 5)		Screen Protector	▶Tempered glass with olephobic coating to reduce smudges. ▶Includes wipes, cleaning cloth and installation instructions.	
KT-MC18-CKEY-20		10-Slot LOCKING Cradle Release Tool	►Used to mechanically unlock the EC30 from the 10-Slot LOCKING Cradle (CRD-EC30-10SLC1-01). ►Pack of 20 keys	
Headset/Audio Accesso	ories			
Part Number	Picture	Description	Notes	Required Items
HDST-35MM-PTT1-01		PTT and VoIP Headset (3.5mm Standard jack)	➤For Push-To-Talk (PTT) and VoIP telephony ➤Uses standard 3.5mm jack. ➤Rotating earpiece allows for right or left ear configuration ➤Built-in cord wrap ➤mono with microphone ➤includes clip for attaching PTT button to clothing.	
HDST-35MM-PTVP-01		PTT Headset (3.5mm Locking jack)	➤For Push-To-Talk (PTT) applications ➤Uses 3.5mm rugged jack that is keyed/collared for a locking failsafe connection. ➤Rotating earpiece allows for right or left ear configuration ➤Built-in cord wrap ➤mono with microphone ➤includes clip for attaching PTT button to clothing.	3.5mm Keyed/Collared Female to 3.5mm Male Headset Adapter Cable (CBL- TC51-HDST35-01)

HDST-25MM-PTVP-01	PTT Headset (2.5mm jack)	*For Push-To-Talk (PTT) applications *2.5 mm jack *Rotating earpiece allows for right or left ear configuration *Built-in cord wrap *mono with microphone *includes clip for attaching PTT button to clothing. *Recommend using 3.5mm headset (HDST-35MM-PTVP-01) instead since this feature provides a more secure locking jack connector.	2.5mm Female to 3.5mm Male Headset Adapter Cable (CBL- TC51-HDST25-01)
SL+1W-3.5WA (3rd party) * https://workforceaudio.com	Workforce Audio SnapLock PTT Adapter Cable	For Push-To-Talk (PTT) applications ◆3.5 mm jack ◆Adapter cable provide SnapLock connector which accepts a variety of Workforce Audio's earpieces. ◆includes clip for attaching PTT button to clothing	Requires purchase of earpiece for connecting to cable.
See HS2100-HS3100 Accessories Document	HS2100 Rugged Wired Headset	*Built to handle the everyday inevitable drops *Dustproof, sprayproof and waterproof *Ready for the freezer and outdoor subzero temperatures *Feather-light for extraordinary comfort *Noise cancellation for a superior voice experience in the noisiest environments *Detachable swivel boom minimizes costs. *Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. *User-replaceable pads and windscreens maximize comfort and hygiene	3.5mm Keyed/Collared Female to 3.5mm Male Headset Adapter Cable (CBL- TC51-HDST35-01) and HS2100 to 3.5mm Standard Cable (CBL-HS2100-3MS1- 01) See HS2100/HS3100 Accessories Document for additional headset accessories
VR12 (3rd party) * http://www.blueparrott.com	BlueParrott VR12 Wired Noise Cancelling Headset	►Audio accuracy for voice picking and other speech recognition applications. ►High quality durability stands up to all-day, every-day use. ►Lightweight design is easy and comfortable to wear all day. ►Compatible with most major wearable computers and devices used in voice-picking environments. ►G type (GN Netcom) Quick Disconnect. ►Convertible design gives choice of over-the-head and behind-the-neck wearing styles.	For 3.5mm Locking jack (recommended): 3.5mm Keyed/Collared Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST35-01) AND RCH50/RCH51 Quick Disconnect Headset Adapter Cable (ADP-35M-QDCBL1-01) For 2.5mm jack: 2.5mm Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST25-01) AND Headset Adapter Cable (25-124387-02R)

RCH51	Rugged Cabled Headset	, 33	For 3.5mm locking jack (recommended): 3.5mm Keyed/Collared Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST35-01) AND RCH50/RCH51 Quick Disconnect Headset Adapter Cable (ADP-35M-QDCBL1-01) For 2.5mm jack: 2.5mm Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST25-01) AND Headset Adapter Cable (25-124387-02R)
RCH50	Rugged Cabled Headset	30C	For 3.5mm locking jack (recommended): 3.5mm Keyed/Collared Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST35-01) AND RCH50/RCH51 Quick Disconnect Headset Adapter Cable (ADP-35M-QDCBL1-01) For 2.5mm jack: 2.5mm Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST25-01) AND Headset Adapter Cable (25-124387-02R)
50-11300-050R	Noise Cancelling Headset	▶Discontinued 8/2011, now use RCH50	For 3.5mm locking jack (recommended): 3.5mm Keyed/Collared Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST35-01) AND RCH50/RCH51 Quick Disconnect Headset Adapter Cable (ADP-35M-QDCBL1-01) For 2.5mm jack: 2.5mm Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST25-01) AND Headset Adapter Cable (25-124387-02R)
3PTY-VXI-VR12 (Zebra orderable SKU) http://www.vxicorp.com	BlueParrot VR12 Wired Noise Cancelling Headset	*Discontinued 10/2018, now use HS2100 series - PMB 10005 *Audio accuracy for voice picking and other speech recognition applications. +High quality durability stands up to all- day, every-day use. *Lightweight design is easy and comfortable to wear all day. *Compatible with most major wearable computers and devices used in voice- picking environments. *G type (GN Netcom) Quick Disconnect. *Convertible design gives choice of over-the-head and behind-the-neck wearing styles	For 3.5mm locking jack (recommended): 3.5mm Keyed/Collared Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST35-01) AND RCH50/RCH51 Quick Disconnect Headset Adapter Cable (ADP-35M-QDCBL1-01) For 2.5mm jack: 2.5mm Female to 3.5mm Male Headset Adapter Cable (CBL-TC51-HDST25-01) AND Headset Adapter Cable (25-124387-02R)

		*HD Voice, also known as Wide Band Audio, brings incredible audio clarity *Built to handle the everyday inevitable drops *Dustproof, sprayproof and waterproof *Ready for the freezer and outdoor subzero temperatures	
See HS2100-HS3100 Accessories Document	HS3100 Rugged Bluetooth Headset	*Feather-light for extraordinary comfort *Noise cancellation for a superior voice experience in the noisiest environments *Swap batteries on the fly — without losing the Bluetooth connection *Split-second tap-to-pair simplicity using NFC. *Detachable swivel boom minimizes costs. *Swivelling boom mutes microphone allowing uses to prevent voice pick applications from recognizing non-voice pick conversations. *User-replaceable pads and windscreens maximize comfort and hygiene *15 hours of battery power	See HS2100/HS3100 Accessories Document for headset accessories
various Bluetooth models B550-XT B350-XT C400-XT C300-XT (3rd party) * http://www.blueparrott.com	BlueParrott Bluetooth Headsets	Various Bluetooth models available with options that include: Blocking out 96% of background noise Over 24 hours of talk time NFC Tap to Pair capable Bluetooth wireless range capable up to 300 ft. Convertible wearing options: over the head, behind the neck. See BlueParrot site for model specific options.	
3PTY-VXI-B350XT (Zebra orderable SKU) http://www.vxicorp.com	BlueParrott Bluetooth Headset for voice directed applications	*Discontinued 10/2018, now use HS3100 series - PMB 10005 *Used to enable Voice Directed Picking (VDP) or Speech Applications in warehouse environments when the use of a wireless headset is desired *Not intended to support peer-to-peer communications (PTT) or VoIP calls. *Provides 24 hours talk time. *Allows the use of other BT devices (i.e. RS6000 scanner or mobile printer) *Zebra Compatible certification for VDP application use with MC32.	
3PTY-VXI-B250XTP (Zebra orderable SKU) http://www.vxicorp.com	BlueParrott Bluetooth Headset for voice directed applications	*Discontinued 10/2018, now use HS3100 series - PMB 10005 *Used to enable Voice Directed Picking (VDP) or Speech Applications in warehouse environments when the use of a wireless headset is desired *Not intended to support peer-to-peer communications (PTT) or VoIP calls. *Provides 20 hours talk time. *Allows the use of other BT devices (i.e. RS6000 scanner or mobile printer)	

3PTY-VXI-EXPWAYII (Zebra orderable SKU) http://www.vxicorp.com		BlueParrott Bluetooth Headset for voice directed applications	Discontinued 10/2018, now use HS3100 series - PMB 10005 *Used to enable Voice Directed Picking (VDP) or Speech Applications in warehouse environments when the use of a wireless headset is desired *Not intended to support peer-to-peer communications (PTT) or VoIP calls. *Provides 8 hours talk time. *Allows the use of other BT devices (i.e. RS6000 scanner or mobile printer) *Zebra Compatible certification for VDP application use with MC92, VC70, WT41 and MC32.	
APTT1 (3rd party) * https://www.aina-wireless.com/	C D C D C D C D C D C D C D C D C D C D	Aina Push-To-Talk (PTT) Bluetooth Voice Responder Remote Speaker/Mic (RSM)	Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ►Includes clip for attaching device to closthing for lapel speaker/mic usage. ►Features several buttons which the application developers can assign to different functions. ►Users can remotely control functions such as push-to-talk, phone calls, channel switching and emergency alerts. ►Device is ruggedized, MIL-STD 810G and IP67. ►Long lasting battery designed for 24 hour approx battery life. Can be recharged via micro-USB port. ►Includes 3.5mm headset jack allowing headphones to be connected for keeping conversations more private. ►Can be easily paired to mobile computer using NFC tap-to-pair.	
H3-B-1 (3rd party) *	wandfu G G	Wandfu H3 Push-To-Talk (PTT) Bluetooth Remote Speaker/Mic (RSM)	▶Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶Includes clip for attaching device to closthing for lapel speaker/mic usage. ▶Includes 3.5mm headset jack allowing headphones to be connected for keeping conversations more private.	

BTR-155 (3rd party) *		Savox BTR-155 Bluetooth Remote Speaker/Mic (RSM)	▶Bluetooth speaker-microphone designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶Includes clip for attaching device to closthing for lapel speaker/mic usage. ▶Rugged wireless speaker microphone, IP55. ▶Allows cable-free movement ▶Familiar speaker microphone functions; PTT and volume buttons ▶Includes 2.5mm headset jack allowing headphones to be connected for keeping conversations more private. ▶LED status indication ▶High speaker volume ▶Includes:	
(Zebra orderable SKU) Discontinued 3/2019, now order from Savox https://www.savoxaccessories.com			- Savox RSM - Modular Wired earpiece - Wall Charger - USB Cable - Quick Start Guide - Carrying Strap	
BTH-101 (3rd party) *		Savox Push-To-Talk (PTT) Bluetooth Headset	▶Bluetooth headset designed to work with different walkie talkie style Push-to-Talk applications, including Zebra PTT Pro (check with Zebra PTT Pro engineering team for current device/OS support). ▶Also operates as standard Bluetooth headset for taking phone calls. ▶Device is lightweight and ruggedized, IP55.	
CBL-HS2100-3MS1-01	×I Y	HS2100 Headset Standard Cable (3.5 mm jack)	▶3.5mm barrel jack connector For use with TC20, TC51/TC56, TC7X, TC8000, or other devices using a 3.5mm barrel jack audio connector Cable is 43" (1.1 M) long Rugged cable with rugged connectors that are keyed/collared for a locking failsafe connection. Includes one clothing clip. Additional clips can be purchased separately.	3.5mm Keyed/Collared Female to 3.5mm Male Headset Adapter Cable (CBL- TC51-HDST35-01)
25-124387-02R		RCH50/RCH51 Headset Adapter Cable	Connects RCH50/RCH51 headset to devices with standard 3-pole 2.5mm barrel jack connector. Updated cable minimizes cross talk and intermittency issues.	2.5mm Female to 3.5mm Male Headset Adapter Cable (CBL- TC51-HDST25-01)
25-124387-01R		RCH50/RCH51 Headset Adapter Cable	Discontinued 9/2013, now use 25- 124387-02R Connects RCH50/RCH51 headset to devices with standard 3-pole 2.5mm barrel jack connector.	2.5mm Female to 3.5mm Male Headset Adapter Cable (CBL- TC51-HDST25-01)

ADP-35M-QDCBL1-01		RCH50/RCH51 Quick Disconnect Headset Adapter Cable	➤ Connects RCH50/RCH51 headset (or headsets with Quick-Disconnect connector) to devices with 3-pole 3.5mm barrel jack connector. ➤ Cable features a rugged keyed/collared jack for a locking failsafe connection.	3.5mm Keyed/Collared Female to 3.5mm Male Headset Adapter Cable (CBL- TC51-HDST35-01)			
CBL-TC51-HDST25-01		2.5mm Female to 3.5mm Male Headset Adapter Cable (2.5mm jack)	►Allows headsets with 2.5mm barrel jacks to be used with EC30. •Converts 3.5mm audio jack to a standard 2.5mm barrel jack connector. •Cable is approximately 6 inches long				
CBL-TC51-HDST35-01		3.5mm Keyed/Collared Female to 3.5mm Male Headset Adapter Cable (3.5mm jack)	Provides a collared/keyed 3.5mm barrel jack connector. Required for use with some headsets (i.e. HS2100) that use a locking keyed connector on the headset jack. Cable is approximately 6 inches long ►Includes Retention/Anti-Rotation Lock (ADP-LOCK-3.5HT1-01)				
ADP-LOCK-3.5HT1-01		Spare/Replacement 3.5mm Audio Adapter Retention and Anti-Rotation Lock	▶This clip is used with the Keyed/Collared Female to Male Headset Adapter Cable (CBL-TC51-HDST35-01) and keyed headset cables to prevent cable rotation/spinning and also to provide a secure, reliable headset connection. ▶Clip is normally included with the Keyed/Collared Female to Male Headset Adapter Cable, this is a spare/replacement clip/lock. ▶NOTE: This is a Spare/Service Parts item. Contact an authorized Zebra reseller to order.				
Power Cords/Power Supplies							
Part Number	Picture	Description	Notes	Required Items			
CBL-DC-388A1-01		DC Power Cord	➤Used along with Power Supply PWR-BGA12V50W0WW to power 2-Slot Charge Cradle (CRD-EC30-2SCHG1-01). ➤Cable length is 1.8 meters				

NOTE: Items highlighted in grey may not be orderable/available

PWR-BGA12V50W0WW	The state of the s	Power Supply	►Used to power 2-Slot Charge Cradle (CRD-EC30-2SCHG1-01). ►100-240 VAC,12V, 4.16A, 50W ►Provides US DOE Level VI compliance for power efficiency. ►Replaces PWRS-14000-148R	DC Line Cord (CBL-DC-388A1- 01) and AC Line Cord (23844- 00-00R)
KIT-PWR-12V50W		Power Supply Kit	►Includes Power Supply (PWR-BGA12V50W0WW) and DC Line Cord (CBL-DC-388A1-01)	AC Line Cord (23844-00-00R)
PWRS-14000-148R		Power Supply with integrated DC Cord	Discontinued 1/2017, now use PWR-BGA12V50W0WW and CBL-DC-388A1-01 - see PMB 2923 and PMB 2851 Replaces KT-14000-148R Used to power 2-Slot Charge Cradle (CRD-EC30-2SCHG1-01). 100-240 VAC,12VDC,3.33A Energy Star Compliant	AC Line Cord (23844-00-00R)
50-14000-148R		Power Supply with integrated DC Cord	Discontinued 12/2007 - replaced by KT-14000-148R +Used to power 2-Slot Charge Cradle (CRD-EC30-2SCHG1-01).	AC Line Cord (23844-00-00R)
KT-14000-148R		Power Supply with integrated DC Cord	➤Replaces 50-14000-148R ➤Used to power 2-Slot Charge Cradle (CRD-EC30-2SCHG1-01). ➤Discontinued 12/2010 - now use PWRS-14000-148R	AC Line Cord (23844-00-00R)
CBL-DC-381A1-01		DC Power Cord	➤ Used to power 10-Slot Cradles when using Level VI Efficiency power supply (PWR-BGA12V108W0WW) ➤ This cable does not include the black extension release latch which is not required when used on Multi-Slot ShareCradles. ➤ CBL-DC-382A1-01 is still typically used though.	
CBL-DC-382A1-01		DC Power Cord	*Used to power 10-Slot Cradles when using Level VI Efficiency power supply (PWR-BGA12V108W0WW) *Cable has black extension tab for releasing the cable from the back of the cradle. This isn't required when using Multi-Slot ShareCradles.	
50-16002-029R		DC Power Cord	►Used to power 10-Slot Cradles	
PWR-BGA12V108W0WW	Elite instance and	Power Supply	▶Replaces PWRS-14000-241R ▶Used to power 10-Slot Cradles ▶9A, 108W ▶Level VI Efficiency rated	DC Power Cord (CBL-DC- 382A1-01) and AC Line Cord (23844-00-00R)

NOTE: Items highlighted in grey may not be orderable/available

PWRS-14000-241R	Power Supply	Discontinued 2/2017, now use PWR-BGA12V108W0WW - PMB 2851 and 2933 Replaces 50-14000-241R Used to power 10-Slot Cradles 100-240VAC,12VDC,9A Energy Star Compliant	AC Line Cord (23844-00-00R)
50-14001-004R	Power Supply	Discontinued 12/2007 - replaced by 50-14000-241R Used to power 10-Slot Cradles	AC Line Cord (23844-00-00R)
50-14000-241R	Power Supply	▶Replaces 50-14001-004R ▶Used to power 10-Slot Cradles ▶Discontinued 12/2010 - now use PWRS-14000-241R	AC Line Cord (23844-00-00R)
23844-00-00R	AC Line Cord	➤ Used with power supplies listed above. ➤ This Line Cord is for use in North America. Refer to the AC Line Cords by Country TAG for comparable cords used in other countries.	
PWR-WUA5V12W0US (US plug style) PWR-WUA5V12W0GB (UK plug style) PWR-WUA5V12W0EU (EU plug style) PWR-WUA5V12W0AU (Australia plug style) PWR-WUA5V12W0CN (China plug style) PWR-WUA5V12W0IN (India plug style) PWR-WUA5V12W0KR (Korea plug style) PWR-WUA5V12W0KR (Korea plug style) PWR-WUA5V12W0BR (Brazil plug style)	USB Power Supply	➤Used with USB-C Cable to provide a lower cost charging solution than using a Cradle. ➤Provides higher current (2.5A) for faster charging ➤100-240 VAC, 5 V, 2.5 A	USB-C Cable (CBL-TC5X- USBC2A-01 or CBL-TC2X- USBC-01)

NOTE: Items highlighted in grey may not be orderable/available