

PM451

BRING SUPERIOR 4G CONNECTIVITY TO YOUR WORKPLACE

Making outdoor tasks easier with LTE connection

The LTE option lets your employees continue to do their tasks without worrying about losing the network connection. Now being able to make data input/output with seamless connectivity on PM451, your workers can handle all warehouse logistics problems with ease - no matter where they are. Expect a fast and consistent WiFi connection anytime as well through 2x2 MU-MIMO technology.

Revolutionize the way you capture data

PM451 is designed to run Android, the operating system of choice when it comes to rugged handheld terminals used in the warehouse. Accompanied by Point Mobile's unique Enterprise Mobility Kit (EmKit[™]), this device provides a fast and seamless user experience, minimizing the time and resources for training your workforce.

Configure the PM451 just as you need it

The standard range 1D/2D imager reads all GS1 symbologies as well as poorly printed barcodes. You can opt for the extra long range imager version with a maximum reading distance of 29 meters (when decoding 100 MILS C39 RFL symbology). Two LED indicators on each side will instantly give you information about scanning. In addition, as an effort to meet various needs of our customers, PM451 will come with three types of keypad options which are Numeric, Function Numeric and Alpha numeric. Finally, the ergonomically designed optional gun grip will further increase the productivity of your workforce.

Outstanding durability for rough warehouse tasks

As a heavy-duty mobile terminal, PM451 is tuned with an IP65 rating and a drop resistance of 2m (MIL-STD 810G). Combined with the ability to survive dramatic temperature changes and many more extreme conditions, PM451 is a device you can always rely on during the hardwork.


Industries

Transport & Logistics Manufacturing & WMS

Accessories

Standard AC/DC Power Adaptor Country Plug USB Type-C Cable Standard Battery (5,700mAh) Stylus LCD Protection Film









PM451-DS13-EN

PM451

PERFORMANCE CHARACTERISTICS Main-Processor Qualcomm[®] SDA660 2.2GHz Octa Core **Operating System** Google Android Android 9 or 11 FOTA (Firmware Over The Air) update (GMS certified) Memory and Storage RAM 4GB ROM (NAND Flash) 64GB 1 Micro SIM slot SIM Sensor Proximity sensor, Light Ambient sensor, Accelerometer PHYSICAL CHARACTERISTICS Dimensions With standard batt. 214.94mm L x 77.26mm W x 39.25mm D 8.46 in. L x 3.04 in. W x 1.55 in D Grip 61.6mm 2.43 in Weight 450g / 15.87oz Display 4.3", IPS panel (480 x 800 pixel) WVGA LED backlight Daylight readable (min 500 nits) Wideviewing angle Multi-touch capacitive Corning Gorilla glass Power STD Battery 5,700mAh Li-ion rechargeable **OPT Battery** 4,000mAh Li-ion rechargeable Back-up Battery 60mAh (10C) Li-ion rechargeable (Hot-Swap) Keypad 3 Keypad options Numeric, Function Numeric, Alpha numeric (backlit keys) keypad (optional) Voice and Audio Built-in microphone and speaker Standard USB 2.0 Type C/OTG Communications (supports battery charging PC, USB memory) Notification LED Power (Charging, Battery Fault) Notification (Message, Scan) Vibration **GLOBAL POSITIONING SYSTEM** GPS WiFi SKU : No GPS Phone SKU : Qualcomm GPS GNSS Receiver Support for GPS, GLONASS, Galileo and Beidou

WIRELESS	
Wireless WAN EDGE/GPRS/GSM WCDMA LTE FDD LTE TDD	900/1800/850/1900 B1/2/4/5/6/8/19 B1/2/3/4/5/7/8/12/13/ 19/20/25/26/28 B38/B40/41
Wireless LAN	
Radio	IEEE 802.11a/b/g/n/ac/d/h/i/k/r/v, IPv4, IPv6, 2x2 MU-MIMO
Data Rates	5GHz: 802.11a/n/ac: Up to 866.7 Mbps 2.4GHz: 802.11b/g/n: Up to 300 Mbps
Operating Channels	1 to 13 (2412~2472MHz) 36 to 165 (5180~5825MHz)
Channel Bandwidth	20, 40, 80 MHz
Security and Encryption	WEP (40 or 104bit) WPA/WPA2 Personal (TKIP, AES) WPA/WPA2 Enterprise (TKIP/AES) WPA3 Enterprise (AES)* WPA3 Enterprise (AES)* WPA3 Enterprise 192-bit mode (GCMP 256)* Enhanced Open (OWE)* PEAP (MSCHAPv2, GTC), TLS, TTLS (PAP, MSCHAP, MSCHAPv2, GTC) PWD, SIM, AKA, AKA', LEAP CCX v4 supported WiFi Direct and Hot spot support
Fast Roam	CCKM, 802.11r
*Supported on Android	
Wireless PAN	
Bluetooth	Integrated Bluetooth Class I, Ver. 5.0 BLE support
DATA CAPTU	JRE
Integrated Barcode	Peader
1D barcode scanner	SE965
2D barcode scanner	N6703
Long range	EX30
Camera	
Тор	13MP with LED flash
NFC (Near Field Co	mmunication)
NFC (Near Field Co NFC-Forum (NFC-IP MODES)	mmunication) Reader For NFC Forum (Tag Types 1 To 5), P2P Active (106 To 424 kbps) Initiator and Target, P2P Passive (106 To 424 kbps) Initiator and Target
Reader (PCD - VCD)	ISO/IEC 14443 A, ISO/IEC 14443 B ISO/IEC 15693, Mifare Classic 1K/4K Mifare DESFire, Mifare UltraLight©, Sony FeliCa
USER ENVIRONMENT	
Operating Temperature	-20°C to 60°C / -4°F to 140°F
Storage Temperature	-40°C to 70°C / -40°F to 158°F

WIRELESS

Temperature

Humidity

95% Non-condensing

Corporate Headquarters

Point Mobile Co., Ltd. pm_sales1@pointmobile.com +82 2 3397 7870

For more information, visit www.pointmobile.com

NA Headquarters Point Mobile Americas LLC info@pointmobileamericas.com +1 425 780 4452

Europe Headquarters Point Mobile Europe GmbH info.pmeg@pointmobile.com +49 211 1588 5913

Multiple drops from 1.8m (6ft) to concrete Drop over the entire operating temperature range Multiple drops from 2m (6.5ft) per MIL-STD 810G at room temperature Rain / Dust Proof (Sealing) IP65 Tumble 1,000 cycle (2,000hits) at 1m / 3.3ft ±15 kV air discharge Flectrostatic Discharge

±8 kV contact discharge

REGULATORY APPROVALS AND COMPLIANCE

Certified CE, CB, RCM, KC, IC, FCC, IFITEL, NOM, NBTC, CU, FAC, NRCan, DOE, CEC Environmental: RoHS III & WEEE compliant

ENTERPRISE SOLUTION

SOTI, Airwatch, Teamviewer

EmKit	
Scan2Stage	PC tool for provisioning Point Mobile Android devices. With Scan2Stage, IT administrator can prepare the settings of the device and make QR code for Scan2Set.
EmKiosk	Kiosk application for Point Mobile devices. IT administrator can restrict the scope of the operator's system execution via EmKiosk to increase productivity and prevent distractions.
Direct Clone	Solution for restoring the devices to the same settings with no internet connection. With Direct Clone, a Master PDA becomes a hotspot server and sends its backup file to nearby client devices to clone the settings.

PULS - ANDROID UPDATE & SECURITY

PULS is Point Mobile's lifetime solution, which extends the life cycle of Android-based Point Mobile enterprise devices to up to seven years after a product launch.

PULS . ^

Patches, Updates & Lifetime Support

Stay up-to-date with the latest updates for 7 years PULS comes free of charge for security patches & updates Get the latest Android version and its newest features Conveniently update your devices in the field by FOTA

For further information, please visit www.pointmobile.com or contact your regional sales representative.

WARRANTY

Subject to the Terms and Conditions, PM451 carries 1 (one) year-warranty period from the date of purchase against the defective materials and manufacturing defects.

For the further inquiry, please contact: service@pointmobile.com

> China Headquarters Point Mobile China info@pointmobile.com.cn +86 755 8869 1169

Google, Android, Google Play and other marks are trademarks of Google LLC. Copyright © 2006-2022 Point Mobile Co., Ltd. All rights reserved. Point Mobile is the designer and manufacturer of handheld mobile computers. The Point Mobile logo is a registered trademark and symbol of Point Mobile Co., Ltd. Features and specifications are subject to change without prior notice.